

# GOT817L-511

17" SXGA TFT IP66 & IP69K-rated Stainless Steel Fanless PCT (or Resistive Touch) Panel Computer with Intel® Core™ i5 Processor and Flat Bezel Design (-20°C to +50°C)

### **Features**

- 17" SXGA TFT flat bezel LCD display
- IP66/IP69K-rated (NEMA 4X) water/dust/corrosion-proof design
- Full stainless steel enclosure with type 316
- -20°C to +50°C wide operating temperature range
- Fanless design with Intel® Core™ i5 processor
- Optional Wi-Fi/3G kit for wireless network connectivity
- 9 ~ 36 VDC wide range power input
- Supports suspension and VESA mount
- M12 type connectors for harsh environments



#### Introduction

The 17 inch GOT817 is specially designed for food processing applications. Its IP66-rated stainless steel housing protects entire system from damage of water, powder and dust. It also supports a wide operating temperature range from -20°C to +50°C. Thus, this robust unit is best suited for extreme humility, dusty or wet spaces in food factories or kitchens and more harsh applications.

#### Full IP66 and IP69K Certified

The GOT817 adopts a water/dust-proof housing design with five IP66-rated connectors, M12 I/O connectors and IP69K that ensures the product's ability to resist ingress of high temperature and high pressure water. It passed entire system IP66 test by SGS, and verified salt mist test. Additionally, it was tested by a spray nozzle with high temperature water ( $+80^{\circ}$ C), a flow rate of 14 ~ 16 L/min and a nozzle hold with distance 10 ~ 15 cm away from the device at angles of 0°, 30°, 60° and 90° for 30 seconds. The GOT815 is qualified to meet harsh environment applications.

#### Wide Temp. (-20°C to +50°C) & Anti-vibration (1G) Design

The GOT817 featuring fanless and noiseless design supports a wide operating temperature range from -20°C to +50°C. Besides, the patent of anti-vibration for SSD ensures system reliability and stability.





- 4. DC Power Connector 5. Ethernet
- 6. COM 1 (RS-232/422/485, default RS-232)
- 7. COM 2 (RS-232/422/485, default RS-232)
- 8. USB 2.0 x 2 9. USB 2.0 x 2

### Specifications

Enclosure	Stainless type 316	
LCD Panel	Display Type	17" SXGA TFT LCD
	Brightness (cd/m <sup>2</sup> )	350 nits LCD
	Resolution	1280 x 1024
	Viewing Angle (H/V)	170°/160°
Main System	CPU	Intel® Core™ i5 7300U 3.5 GHz
		(Kaby Lake)
	Chipset	SoC Integrated
	System Memory	1 x 260-pin DDR4-2133
		SO-DIMM, up to 16GB
	BIOS	AMI UEFI BIOS
	Storage	1 x 2.5" SSD HDD or 1 x 2.5" SATA
		HDD
	Watchdog Timer	255 levels, 1 ~ 255 sec.
	Onboard Graphics	Integrated in Intel® GFX

\* All specifications and photos are subject to change without notice



### **Specifications**

I/O Connector	2 x RS-232/422/485 (default RS-232, A-coded) 4 x USB 2.0 (A-coded) 1 x 10/100/1000 Mbps Ethernet supporting PXE and LAN wake-up (Intel® I210-IT; X-coded)	
Expansion Interface	1 x full-size PCI Express Mini Card slot 1 x falf-size PCI Express Mini Card slot	
Touchscreen	5-wire resistive touch or projected capacitive multi-touch	
Power Supply	Power input 9 ~ 36VDC	
Power Consumption	TBD	
Dimensions	TBD	
Packing Dimensions	TBD	
Weight (net/gross)	TBD	
Environment	Operating temperature: -20°C ~ +50°C (-4°F ~ +122°F) Relative humidity: 10% ~ 95% @ 40°C, non-condensing Operation vibration: 1G, 5 ~ 500Hz, random for 2.5" SSD	
Certificate	CE	

**Ordering Information** 

GOT817L-511-C-DC	17" SXGA fanless IP66 & IP69K-rated stainless steel touch panel computer with Intel® Core™ i5-7300U, projected capacitive touch screen, 420 nits LCD and 9 ~ 36 VDC power input
GOT817L-511-C-RF-DC	17" SXGA fanless IP66 & IP69K-rated stainless steel touch panel computer with Intel® Core™ i5-7300U, projected capacitive touch screen, 420 nits LCD and 9 ~ 36 VDC power input and Wi-Fi/3G
GOT817L-511-R-DC	17" SXGA fanless IP66 & IP69K-rated stainless steel touch panel computer with Intel® Core™ i5-7300U, 5-wire flat resistive touch screen, 9 ~ 36 VDC power input
GOT817L-511-R-RF-DC	17" SXGA fanless IP66 & IP69K-rated stainless stell touch panel computer with Intel® Core™ i5-7300U, 5-wire flat resistive touch screen, 9 ~ 36 VDC power input and WiFi/3G

### Optional Accessories

594B8122100E	Water-proof COM cable (1.8m)
594B8152710E	Water-proof LAN cable (1.8m)
594B8122820E	Water-proof USB cable (1.8m)
50966D45010E	Adapter 24V 120W, M12 A-code 5P, LTE120ES
822B8120070E	GOT812 keyboard bracket (w/o keyboard)

#### **Optional EOS Installation**

Windows® 10 IoT

### **Optional OS Installation**

Windows® 10

\* All specifications and photos are subject to change without notice.

© 2018 Axiomtek Co., Ltd. All rights reserved.

502



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660