



EMX-BSWP

Intel® Celeron® N3160 Processor Thin Mini ITX Motherboard

- > Intel® Celeron® N3160 Processor (2M Cache, up to 2.24 GHz)
- > 2 x 204-pin DDR3L 1600 MHz SO-DIMM supports up to 8GB
- > VGA, HDMI, Dual channel 18/24-bits LVDS
- > 2 x Intel® i211AT Gigabit Ethernet
- > Realtek ALC662 Audio Codec
- > Realtek ALC105 Stereo Class-D 3W x2 Audio Amplifier
- > 1 x Mini PCI-e Supported mSATA, 1 Mini PCI-e, 1 x PCI-e
- > 2 x SATA III, 2 x SATA Power, 4 x USB 2.0, 4 x USB 3.0
- > 5 x RS232, 1 x RS232/422/485, 8-bit GPIO
- > Mic-in, Line-out, 1 S/PIDF, SD card slot, Optional Infineon SLB9665 TPM 2.0
- > Onboard eMMC (Optional 32GB)
- > DC in +12V

Spec

| System | |
|------------------------------|---|
| Processor | Intel® Celeron® N3160 Processor (2M Cache, up to 2.24 GHz) |
| System Memory | 2 x 204-pin DDR3L 1600 MHz SO-DIMM supports up to 8GB |
| I/O Chip | EC ITE IT8528E |
| BIOS | AMI 64Mbit SPI BIOS |
| Watchdog Timer | H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step |
| H/W Status Monitor | Monitoring System Temperature and Voltage with Auto Throttling Control |
| Expansion | |
| Expansion | 1 x PCI-e 1 x Mini PCI-e Supports mSATA (Switch Through Jumper) 1 x Mini PCI-e 1 x SD card slot Supports SD/SDHC Card 1 x SIM card slot |
| I/O | |
| USB | 4 x USB 2.0 4 x USB 3.0 |
| SATA | 2 x SATA Power 2 x SATA III |
| COM Port | 5 x RS232 1 x RS232/422/485 |
| DIO | 1 x 8-bit GPIO |
| Other | 1 x S/PIDF |
| Display | |
| Chipset | Intel® Celeron® SoC integrated Graphics |
| Resolution | VGA: 2048 x 1536 @ 60Hz HDMI: 3840 x 2160 @ 30Hz LVDS: 1920 x 1080 @ 60Hz |
| LVDS | 2CH 18/24bits LVDS 1920 x 1080 Chrontel. CH7511B eDP to LVDS Converter |
| Multiple Display | HDMI + LVDS +VGA |
| Audio | |
| Chipset | Realtek ALC662 supports 2-CH |
| Audio Interface | Mic-in, Line-out |
| Audio Amplifier | 2 x Stereo Class-D 3W Audio Amplifier |
| Ethernet | |
| Chipset | 2 x Intel I211AT Gigabit Ethernet |
| Ethernet Interface | 10/100/1000 Base-Tx GbE compatible |
| LAN Port | 2 x RJ45 |
| Mechanical & Environmental | |
| Power Requirement | +12V |
| Power Type | AT/ATX |
| Operating Temperature | 0 ~ 60°C (32 ~ 140°F) |
| Storage Temperature | -40 ~ 75°C (-40 ~ 167°F) |
| Operating Humidity | 0 ~ 90% Relative Humidity, Non-condensing |
| Dimension (L x W) | 6.69" x 6.69" (170mm x 170mm) |
| Weight | 0.88lbs (0.4Kgs) |

Ordering

EMX-BSWP-A1R
Intel® Celeron® N3160 Processor Thin Mini ITX Motherboard

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660