

# FCH2205D-WMA0L

## Specification

**IP66, Stainless Chassis 22" LCD Monitor, 1680x1050,  
LED BLU 1000nits**



### Features

- Modular mechanism design provides flexible product configuration and easy maintenance.
- Stainless Steel Enclosure
- Option with auto-brightness sensor offers application in day and night.
- Option to built-in touch screen for interactive application.

|                     |  |   |  |
|---------------------|--|---|--|
| Panel               | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating          |  |
|                     | Aspect Ratio / Size  | Wide / 22" viewable diagonal area                           |  |
|                     | Active Area / Pixel Pitch  | 473.8(H) x 296.1(V) mm / 0.282(H) x 0.282(V) mm             |  |
|                     | Native Resolution / Colors   | 1680(H) x 1050(V) / 16.7 Million                            |  |
|                     | Brightness / Contrast  | 1000 cd/m <sup>2</sup> (typ) / 700 : 1                      |  |
|                     | Response Time  | ≤ 5 ms  |  |
|                     | Viewing Angle (typical)  | H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)            |  |
|                     | Light Source   | LED BLU, Long life, 30,000 hrs (typ)                        |  |
| Input Sources       | PC System  | Signal  | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)          |
|                     |  | Sync  | Separate Sync, Composite Sync, Sync On Green             |
|                     |  | Frequency   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 - 75Hz |
|                     | Audio System   | 2W speaker x 2  |  |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |   |  |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |   |  |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA 200 x 200 mm)                               |   |  |
| Power               | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz           |   |  |
| Power Consumption   | Operation / Power Saving   | 18 watt , < 2 watt (Support DPMS)                           |  |
| Operating Condition | Temperature / Humidity   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |  |
| Storage Condition   | Temperature / Humidity   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |  |
| Certification       |  | FCC , CE  |  |
| Dimensions          | Physical   | With Base(W x H x D) : TBD                                  |  |
|                     |  | Without Base(W x H x D) : 579.7 x 406.1 x 86.0 (mm)         |  |
|                     | Carton   | W x H x D = 556 x 450 x 160 (mm)                            |  |
| Weight              | N.W. / G.W.  | 15.0 Kgs / 17.0 Kgs   |  |
| Container Loaded    | 20ft / 40ft / 40ft HQ  | TBD (Sets , By pallet)                                      |  |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |

**Winsonic**<sup>®</sup>

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com  
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

[www.ewinsonic.com](http://www.ewinsonic.com)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660