

## Aplex Technology ViTAM-921BR Get Quote

iTAM-921BPR(H)	21.5" IP66 / IP	69K Stainless Steel	Panel PC		ndustrial Panel PC	HMI Controller	Industrial Display Monitor
	Features /			Dimensio	ons ( 💭		
	<ul> <li>21.5" New Generation Stainless Steel Panel PC</li> <li>Bth Gen. Intel Core 13/5 BGA type Processor</li> <li>Ture Flat Front Bezel Design and Grade 304 Stainless Steel Enclosure (Grade 316 for Option)</li> <li>IP66/IP69K Rated with M12 Connectors</li> <li>Support Resistive Touch, Projected Capacitive Touch</li> <li>Touch on/off Button on the Side Edge for Hygienic Cleaning</li> <li>Support Ergonomic Versatile Mounting: Yoke Mounting / Space-saving VESA 100 x 100 mm Mounting</li> </ul> Specifications           System         Core 15-8365UE(Quad Core, 6 MB cache, 1.6GHz) Core 13-8145UE(Dual Core, 4 MB cache, 2.2GHz)				<u>5718</u> 5718 4778		
	System Chipset Memory TPM	SoC 2 x 260-pin SO-DIMM up to Firmware TPM (TPM 2.0 con	64GB DDR4 2400MHz				
· · · · · · · · · · · · · · · · · · ·	IO Port USB Serial / Parallel LAN Others					}	UNIT: mm Tolerance:±0.5
	Power Connector	nector 1 x M12 3-pin for DC power with waterproof cover and chain					
	Option	1 x Power switch on the rear 2 x optional blank M12 connector with waterproof cover and chain for selecting two from the following options: 2 x USB 2.0 1 x USB 3.2 Gen.1 1 x LAN 1 x COM 1 x CAN		Power         DC 9~36V           Power Input         DC 9~36V           Power Consumption         ViTAM-921BP: 40W           Mathematical State Construction         304 Stainless steel chassis(default), 316 Stainless steel chassis(optional)           Mounting         VESA mount 100 x 100, Yoke mount for optional			
	Storage Space			Mounting IP Rating	VESA mount 100 x 100 Total IP66/IP69K	Yoke mount for optional	
	HDD	1 x 2.5" SATA3 HDD (for opt	tion)	Dimensions	571 x 362 x 55 mm		
	M.2	1 x B-key 2280 (SATA as de	fault, PCI-e select by BIOS) for SSD	Net Weight	10.0 kg		
	Expansion			Environmental			
	Expansion slot	1 x Full size mSATA/mPCle (mSATA as default, select by BIOS) 1 x NANO-SIM 1 x M.2 E-key 2230 (PCle+USB) for optional WIFI/BT module		Operating Temperating Temperat		-condensing	
	RFID module	RFID module design on the front side (for option)		Certificate	CE/FCC Class A	5	
	Display	Standard	High Brightness Optional	Operating Syste	m Support		
	Display Type	21.5" TFT-LCD	21.5" TFT-LCD	Windows 10 IoT E	ENT LTSB, Windows 11		
	Max. Resolution	1920 x 1080	1920 x 1080	Ordering Inform	ation		
	Max. Color Luminance (cd/m <sup>2</sup> )	16.7M 250	16.7M 1000			I panel pc, Intel 8th Gen. Core i Processor,	
	View Angle	178(H) /178(V)	178(H) /178(V)	VITAM-921BP	2 x SO-DIMM DDR4 slots, 128GB TI	C SSD, projected capacitive touch, 9~36V	
	Contrast	3000:1	3000:1		DC power input with Adapter		
	Backlight Lifetime	30,000 hrs	50,000 hrs	21.5" FHD IP66/IP69K stainless steel panel pc, Intel 8th Gen. Core i Processor, VITAM-921BR 2 x SO-DIMM DDR4 slots, 128GB TLC SSD, 5 wire resistive touch window, 9~36V			av.
	Touch Screen				DC power input with Adapter		
	Туре	Resistive Touch (for BR mod Projected Capacitive (for BP		21.5° FHO IP66/IP69K stainless steel panel pc, Intel 8th Gen. Core i Processor, ViTAM-921BPH 2 x SO-DIMM DDR4 slots, 128G8 TLC SSD, projected capacitive touch, 9–36V DC power input with Adapter, 1000 nits			
	Interface	USB		21.5" FHD IP66/IP69K stainless steel panel pc, Intel 8th Gen. Core		I panel pc, Intel 8th Gen. Core i Processor,	
	Light Transmission(%) Resistive Touch : 80% Projected Capacitive : 90%			VITAM-921BRH 2 x SO-DIMM DDR4 slots, 128GB TLC SSD, 5 wire resistive touch window, 9~36V DC power input with Adapter, 1000 nits			NV .
		-					



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660