

AVerMedia

AVerGrabber CN312S

2K SDI Dual-Channel M.2 Video Capture Card

CN312SW
CN312SC

Wide Temperature Version
Wide Temperature with Conformal Coating Version



Features

- Max. input resolution 2048 x 1080 60fps
- Max. capturing/ recording 1920 x 1080 60fps
- The latest M.2 compact interface
- Hardware video processing:
 1. hardware scaling
 2. color space conversion
- Wide temperature and conformal coating design

Introduction

AVerMedia AVerGrabber CN312S, the 2K SDI Dual-Channel M.2 Video Capture Card, is equipped by two SDI channels with the embedded audio. With its SDI video source input, it is able to support an astounding uncompressed real-time video capture resolution of up to 2K (2048 x 1080). At the frame rate of 60 fps, CN312S can improve the quality of a wide range of media recorded for businesses, universities, broadcasting, and manufacturing facilities, which can eventually provide a more lifelike and smooth video playback experience.

CN312S is a PCIe Gen2 x2 M.2 capture card equipped with 2 SDI channels with embedded audio input. With its SDI video source input, it is able to support an astounding uncompressed real-time video capture resolution of up to 2K (2048 x 1080 60fps).

Along with M.2 cards' compact size and AVerMedia proprietary SDK, it can be seamlessly integrated into vertical applications that require ultra high-definition video quality such as industrial, medical, education, video conference, etc. Utilizing software encoding, it offers users the customization ability to tweak or modify codecs' decompression and compression settings for optimum bit-rate or video quality. With AVerMedia Windows and Linux driver support, clients are able to choose from a wide range of platforms according to your needs; making CN312S the best choice for all ultra-HD professional capturing applications.

Wide Temperature and Conformal Coating Design

AVerMedia delivers this advanced solution, which is capable of withstanding the extreme temperature environment without compromising the video functionality. CN312SW (Wide Temperature Version) can offer the stable operation in the temperature range from -20°C to 70°C (-4°F to 158°F). Furthermore, CN312SC (Wide Temperature with Conformal Coating Version) thermally robust product is specifically designed to provide great reliability for the rugged and industrial applications to against moisture, dust, or chemicals.

Hardware Scaling and Color Space Conversion

AVerMedia hardware-based video engine technology implements practical video processing functions such as color space conversion for more true-to-life video color and resolution scaling. The functions help reduce the computing burden on hardware and software in order to focus on other important applications at hand.

AVerGrabber CN312SW/CN312SC

2K SDI Dual-Channel M.2 Video Capture Card

Thermal Design



Specifications

Host Interface	Gen2 x 2
Audio Format	SDI embedded audio
Audio Sampling Rate	48KHz
Connector Type	BNC for SDI
Input Interface	2-channel 2K SDI
Video Format	Driver support output: 4:2:0 8-bit : NV12, I420, YV12 4:2:2 8-bit : YUY2 4:4:4 8-bit: IYU2, BGR24, BGR32 SDK support output: 4:2:0 8-bit : YV12 4:2:2 8-bit : YUY2 4:4:4 8-bit: BGR24
Color Depth	8-bit (support 10-bit video input)
Channel No.	2 channels
Max. Input Resolution	2048 x 1080@60fps
Max. Capturing Resolution	1920 x 1080@60fps (2-channel)

Encoding Mode	Software encoding
Multi-Card Support	Yes
Supported OS	Windows 7/ 8.1/ 10 (32/ 64 bit) Linux (based on V4L2, support x86, x64)
Form Factor	M.2 (2280 Key M)
Dimension (W x L x H)	22 x 80 x 26.3 mm
Power Consumption	3.3 W
Operating Temperature	CN312SW: -20°C ~ 70°C CN312SC: -20°C ~ 70°C (with 0.5m/s airflow)
Operating Humidity	0% ~ 95% relative humidity
Storage Temperature	-40°C ~ 85°C
Safety Certification	FCC / CE

*All specifications are subject to change without prior notice.

Versatile SDK

AVerMedia Software Development Kit (SDK) is a set of development tools that allows software engineers to seamlessly integrate video capture modules into application-specific systems. SDK Pro and SDK Premium are available upon request, they offer professional grade functionalities to better match each application's specific requirements.

Ordering Information

- **CN312SW:** Wide Temperature Version
- **CN312SC:** Wide Temperature with Conformal Coating Version
- **Package includes:**
 - CN312S
 - BNC cable x 2
- **SDK kits:**
 - SDK Pro
 - SDK Premium add-on kits

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660