

AEx-2410	Intel Celeron Processor N2930 Stainless Steel Box PC	Industrial Panel PC HMI Controller Display Monitor Box PC
	<ul> <li>Features</li> <li>Intel Celeron N2930 Processor</li> <li>SUS 316 Stainless Steel</li> <li>Total IP66 Grade with M12 Waterproof Connector</li> <li>Variety of IO applications</li> <li>WLAN for Option</li> <li>Wide range DC 9~36V Power Input</li> <li>Support Panel Mount &amp; VESA Mount</li> <li>Fanless Design</li> <li>ATEX Zone2, IECEx and C1D2 Certified</li> </ul>	Dimensions / 2
	System         CPU       Onboard Intel Celeron N2930 Processor (2M Cache, 1.83GHz         System Chipset       Soc         Memory       Onboard 4GB DDR3L SDRAM (optinon)         IO Port       USB         USB       1 x M12 8-pin for 2 x USB 2.0 with waterproof cover and chain         Serial/Parallel       1 x M12 8-pin for COM1, RS-232/422/485, default RS-232, with waterproof cover and chain         Graph       1 x M12 8-pin for LAN with waterproof cover and chain         LAN       2 x M12 8-pin for DC power with waterproof cover and chain         Power       1 x M12 3-pin for DC power with waterproof cover and chain         Storage       1 x 2.5" SATA3 HDD space         Movable device       1 x internal SD card slot onboard	
	Expansion           Expansion Slot         1 x Mini-PCIe slot (full size) for option WLAN/BT module           Power         Power Input         DC 9~36V           Power Consumption         MAX: 15.9W           Mechanical         Construction         316 Stainless Steel Chassis           Mounting         VESA mount 100 x 100, Wall mount         IP Rating           Total IP66         Dimensions         334 x 195 x 38.5mm           Net Weight         4.0 kg         Ket Max 200, Ket M	Operating System Support Windows 7 Pro for Embedded Windows Embedded Standard 7 Windows Embedded 8.1 Industry Pro Windows Embedded 8 Standard Windows 10 IoT ENT LTSB
	Environmental           Operating Temperature         -20~ 60°C           Storage Temperature         -30~ 70°C           Storage Humidity         10 to 90%@ 40°C, non-condensing           CE / FCC Class A         A           ATEX Zone 2E xn All CT 4 Gc         Class 1, Division 2, Group ABCD T4           ANS/I/SA 12.12.012013         CSA Std. C222. No213-1887	Ordering Information         Fanless Box PC module, Intel Celeron N2930 1.8G CPU fan less panel PC, 8GB DDR3L memory on board, 1 x 128GB 2.5" MLC SSD, 1 x 64GB mSATA GMLC SSD, Projected capacitive touch, DC9-36V power input with power adapter, 316 stainless steel enclosure, support VESA Mount, WT-20-60 Accessary : 1 x M12 for 2 x USB2.0 Cable, 2 x M12 LAN cable, 1 x M12 COM Cable, 1 x VGA Cable, 1 x 3pin power input table (w/o Adapter)



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660