



ARC-1509-B

15" Intel® Celeron® J1900 Fanless Rugged Touch Panel PC with IET Expansion

- > Onboard Intel® Celeron® J1900 4-Core 2.0GHz processor
- > Full Flat Front Panel with Projected Capacitive Touch Supports Multi Touch
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB DDR3L 1333 SDRAM
- > 4 USB, 2 COM
- > Dual Intel I211AT Gigabit LAN
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Available Expansion for Audio, USB, COM, HDMI, MPCle, GPIO, CAN Bus
- > IP65 Compliant Front Panel, IP41 Rear Box
- > With Panel Mount kits included
- > TPM 1.2 Function (Optional)

+ Spec

-System Information-	
Processor	Intel® Celeron® J1900 4-Core 2.0GHz processor
System Memory	1 x 204-Pin DDR3L 1333MHz SO-DIMM up to 8 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec. and 1sec./step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
SBC	ARC-BYT
Expansion	
Expansion	1 x Mini PCIe Supports mSATA 1 x 80-pin IET interface
Storage	
Storage	1 x 2.5" Drive Bay (7mm HDD Restricted)
Panel	
LCD Size	15",4:3
Display Type	XGA
Resolution	1024x768
Pixel pitch	0.297mm(H) x 0.297mm(V)
Luminance	300 cd/m ²
Contrast ratio	2000
Viewing angle	88 (U), 88 (D), 88 (L), 88 (R)
Response time	16 ms
Backlight	LED
Touch Type	Projective Capacitive Multi-Touch up to 10 points
Touch Light Transmission	89 %
Touch Controller	USB touch (EETI)
I/O	
USB Port	1 x USB 3.0 3 x USB 2.0
COM Port	1 x RS-232/422/485 1 x RS-232
SATA	1 x SATA II
Other	3 x Knockouts for Antenna Mounting
Display	
Graphic Chipset	Intel® Valleyview SoC integrated Graphics Supports optional dual display
Spec. & Resolution	HDMI: Max. resolution 1920x1200 @ 60Hz (Optional by IET module)
Audio	
Audio Codec	Realtek ALC888S
Audio Interface	Speaker Out
Speaker Output	2 x 2W
Certifications	
Certification Information	CE FCC Class B
Ethernet	
LAN Chipset	2 x Intel® I211AT
Power Requirement	
DC Input	+12V ~ +26V
DC Input Connector	Lockable DC Jack



Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	350 x 274.5 x 53 mm
Weight	3.7 Kgs
Vibration Test	With SSD/mSATA : 3Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
Shock Test	Operating with SSD/CFast/mSATA : MIL-STD-810G, Method 516.6, Procedure I, functional shock=20G
Mounting Kit	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm Panel Mount with mounting kits
Power Mode	AT/ATX (ATX is default setting)
System Fan	Fanless
Construction - Front	Die Casting with Cover lens
Construction - Rear	Black Die Casting
Software Support	
OS Information	Win 7/8.1 / 10 / Linux
Ordering Information	
Ordering Information	<p>ARC-1509-190-B3-1R 15" 1024x768 Industrial Touch Panel PC, ErP Design (D1 stepping CPU) Intel Celeron SoC J1900 2.0GHz CPU/2GLAN/2COM/4USB/SPK/12~26V input/12V Adapter</p> <p>Optional IET Module list:</p> <p>ACC-ARC-USB-1R 4 x USB 3.0 Kit for ARC Series</p> <p>ACC-ARC-AUDIO-1R HDMI + 5.1 CH Audio Kit for ARC Series</p> <p>ACC-ARC-MPCIE-1R HDMI + MPCIE w/SIM Kit for ARC Series</p> <p>ACC-ARC-COM-1R 2 x Isolated RS-232 Kit for ARC Series</p> <p>ACC-ARC-COM-2R 3 x RS-232 Kit for ARC Series</p> <p>ACC-ARC-COM-3R 2 x RS-232 + USB Kit for ARC Series</p> <p>ACC-ARC-COM-4R 2 x RS-232 + LAN Kit for ARC Series</p> <p>ACC-ARC-GPIO-1R 12-bit GPIO + 2-pin CAN Bus Kit for ARC Series</p> <p>ACC-ARC-OBDII-1R OBDII - CAN Bus Kit for ARC Series (OBDII/EOBD for Small Vehicle)</p> <p>ACC-ARC-OBDII-2R OBDII - CAN Bus Kit for ARC Series (J1939J1708 for Large Vehicle)</p> <p>ACC-ARC-OBDII-3R OBDII - CAN Bus Kit for ARC Series (ISO15765-4 for Special Large Vehicle)</p> <p>E1702031833R USA Power Cord</p> <p>E1702031000R EU Power Cord</p> <p>E1702031834R Japan Power Cord</p> <p>E1702031830R UK Power Cord</p> <p>E1702031831R Australia Power Cord</p>

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660