

VITAM-921AR/P/G(H)

21.5" IP66 / IP69K Stainless Steel Panel PC

Industrial Panel PC



Features /

- 21.5" New Generation Stainless Steel Panel PC
- 6th Gen Intel Core i3-6100U / Core i5-6300U Onboard Processor
- True Flat Front Bezel Design and Grade 304 Stainless Steel Enclosure (Grade 316 for Option)
- IP66/IP69K Rated with M12 Connectors
- Support Resistive Touch, Projected Capacitive Touch, and Glass
- Touch on/off Button on the Side Edge for Hygienic Cleaning
- Support Ergonomic Versatile Mounting: Yoke Mounting / Space-saving VESA 100 x 100 mm Mounting



Specifications /

System	
CPU	Onboard 6th Gen Intel Core i3/i5 Processor
System Chipset	SoC
Memory	1 x 260-pin SO-DIMM up to 16GB DDR4 2133MHz
IO Port	
IO POIL	
USB	1 x M12 8-pin for USB 2.0 with waterproof cover and chain
Serial / Parallel	1 x M12 8-pin COM1, RS-232/422/485, default RS-232, with waterproof cover and chain
LAN	1 x M12 8-pin for LAN with waterproof cover and chain
Others	1 x Touch on/off button on the side
D 0	1 x M12 3-pin for DC power with waterproof cover and chain
Power Connector	1 x Power switch on the side
	2 x optional blank M12 connector with waterproof cover and chai for selecting two from the following options: 2 x USB 2.0
Option	1 x USB 3.0 1 x LAN (POE for option)


Storage Space		
HDD	1 x 2.5" SATA3 HDD	
Expansion		
Expansion Slot	1 x miniPCle slot for WIFI/BT(optional), 4G/LTE(optional)	
RFID module	REID module design on the front side(optional)	


1 x COM

Dispalay	Standard	High Brightness Optional
Display Type	21.5" TFT-LCD	21.5" TFT-LCD
Max. Resolution	1920 x 1080	1920 x 1080
Max. Color	16.7M	16.7M
Luminance (cd/m²)	300	1000
View Angle	178(H) /178(V)	178(H) /178(V)
Contrast	3000:1	3000:1
Dooklight Lifetime	30 000 bre	50 000 bre

	Backlight Lifetime	30,000 hrs	50,000 hrs
ĺ	Touch Screen		
	Туре	Resistive Touch (For R model Projected Capacitive Touch (F Glass (For G model)	
	Interface	USB	
	Light Transmission(%)	Resistive Touch : 80% Projected Capacitive : 90%	
	Power		
	Power Input	DC 9~36V	
	Power Consumption	ViTAM-921AP:43W	









UNIT: mm Tolerance:±0.5

Mechanical	
Construction	304 Stainless steel chassis(default), 316 Stainless steel chassis(optional)
Mounting	VESA mount 100 x 100, Yoke mount for optional
IP Rating	Total IP66/IP69K
Dimensions	571 x 362 x 55 mm
Net Weight	10.0 kg

Environmental	
Operating Temperature	0~50°C (21.5" High Brightness LCD Model: 0~40°C)
Storage Temperature	-30~70°C
Storage Humidity	10 to 90% @ 40°C, non- condensing
Certificate	CE/FCC Class A

Operating	System	Support

Windows Embedded 7, Windows Embedded 8.1, Windows 10 IoT ENT LTSB

	Ordering Information		
	ViTAM-921AP	21.5" FHD IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, projected capacitive touch, 9~36V DC power input with Adapter	
	ViTAM-921AR	21.5" FHD IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, 5 wire resistive touch window, 9~36V DC power input with Adapter	
	ViTAM-921AG	21.5" FHD IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, protection glass, 9~36V DC power input with Adapter	
	ViTAM-921APH	21.5" FHD IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, projected capacitive touch, 9~36V DC power input with Adapter, 1000 nits	
	ViTAM-921ARH	21.5" FHD IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, 5 wire resistive	

touch window, 9~36V DC power input with Adapter, 1000 nits 21.5" FHD IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i ViTAM-921AGH Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, protection glass, 9~36V DC power input with Adapter, 1000 nits

Industrial Panel PC

Industrial Panel PC

All specifications and photos are subject to change without notice

All specifications and photos are subject to change without notice

V 1.4



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660