

ViTAM-919AR/P/G(H)

19" IP66 / IP69K Stainless Steel Panel PC

Industrial Panel PC



Features /

- 19" New Generation Stainless Steel Panel PC
- 6th Gen Intel Core i3-6100U / Core i5-6300U Onboard Processor
- True Flat Front Bezel Design and Grade 304 Stainless Steel Enclosure (Grade 316 for Option)
- IP66/IP69K Rated with M12 Connectors
- Support Resistive Touch, Projected Capacitive Touch, and Glass
- Touch on/off Button on the Side Edge for Hygienic Cleaning
- Support Ergonomic Versatile Mounting: Yoke Mounting / Space-saving VESA 100 x 100 mm Mounting




Speci


fications	/	1
		_

System			
CPU	Onboard 6th Gen Intel Core is	Onboard 6th Gen Intel Core i3/i5 Processor	
System Chipset	SoC		
Memory	1 x 260-pin SO-DIMM up to 1	1 x 260-pin SO-DIMM up to 16GB DDR4 2133MHz	
IO Port			
USB	1 x M12 8-pin for USB 2.0 with waterproof cover and chain		
Serial / Parallel	1 x M12 8-pin COM1, RS-232/422/485, default RS-232, with waterproof cover and chain		
LAN	1 x M12 8-pin for LAN with waterproof cover and chain		
Others	1 x Touch on/off button on the side		
Power Connector	1 x M12 3-pin for DC power with waterproof cover and chain 1 x Power switch on the side		
Option	2 x optional blank M12 connector with waterproof cover and chain for selecting two from the following options: 2 x USB 2.0 1 x USB 3.0 1 x LAN (POE for option) 1 x COM 1 x CAN		
Storage Space			
HDD	1 x 2.5" SATA3 HDD		
	I X 2.5 SAIAS HDD		
Expansion			
Expansion Slot	1 x miniPCle slot for WIFI/BT(optional), 4G/LTE(optional)		
RFID module	RFID module design on the front side(optional)		
Dispalay	Standard	High Brightness Optional	
Display Type	19" TFT-LCD	19" TFT-LCD	
Max. Resolution	1280 x 1024	1280 x 1024	
Max. Color	16.7M	16.7M	
Luminance (cd/m²)	350	1000	
View Angle	170(H) /165(V)	170(H) /160(V)	
Contrast	1000:1	14441	
		** *** *	

Contrast	1000:1	1000:1
Backlight Lifetime	50,000 hrs	30,000 hrs
Touch Screen		
Туре	Resistive Touch (For R model Projected Capacitive Touch (F Glass (For G model)	
Interface	USB	
Light Transmission(%)	Resistive Touch : 80% Projected Capacitive : 90%	
Power		
Power Input	DC 9~36V	
Power Consumption	ViTAM-919AP:49W	

Dimensions /





UNIT: mm Tolerance: ±0.5

Mechanical	
Construction	304 Stainless steel chassis(default), 316 Stainless steel chassis(optional)
Mounting	VESA mount 100 x 100, Yoke mount for optional
IP Rating	Total IP66/IP69K
Dimensions	470 x 388 x 60 mm
Net Weight	9.5 kg

Environmental	
Operating Temperature	0~50°C
Storage Temperature	-30~70°C
Storage Humidity	10 to 90% @ 40°C, non- condensing
Certificate	CE/FCC Class A

Operating System Support
Vindows Embedded 7, Windows Embedded 8.1, Windows 10 IoT ENT LTSB

Oradining innon	
ViTAM-919AP	19" SXGA IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor 1 x SO-DIMM DDR4 slot, 32G MLC SSD, projected capacitive touch, 9~36V DC power input with Adapter
ViTAM-919AR	19" SXGA IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, 5 wire resistive touch window, 9~36V DC power input with Adapter
ViTAM-919AG	19" SXGA IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, protection glass, 9~36V DC power input with Adapter
ViTAM-919APH	19" SXGA IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, projected capacitive touch, 9~36V DC power input with Adapter, 1000 nits
ViTAM-919ARH	19" SXGA IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, 5 wire resistive touch window, 9~36V DC power input with Adapter, 1000 nits

19" SXGA IP66/IP69K stainless steel panel pc, Intel 6th Gen. Core i ViTAM-919AGH Processor, 1 x SO-DIMM DDR4 slot, 32G MLC SSD, protection

glass, 9~36V DC power input with Adapter, 1000 nits

V 1.5

Industrial Panel PC

Industrial Panel PC

All specifications and photos are subject to change without notice.

All specifications and photos are subject to change without notice



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660