

Hisense

75" High Brightness Display



75WF25E 75" WINDOW FACING - HIGH BRIGHTNESS DISPLAY

Easy to install Window Facing Digital Signage Display's maximise customer engagement with vivid their image quality. With ultra high brightness of 2500 nits, the Hisense window facing displays will attract attention in any lighting condition.

Highlights

Warranty



Round-the-clock operation

Designed with quad-core System on Chip (SoC) technology the window facing display can be used as reliable digital signage displays for both offline and cloud based content.

<u>`</u> مٰ`
2500

2500 nits

With 2500 nits maximum brightness, the panels are 3500 well equipped to make your content vividly stand out in any commercial location. We also have 3500 and 4500 nit window facing displays available to special order. Please contact your Hisense representative for more details.



Visible With Polarized Sunglasses

2,500 nits LCD to give you a clear image, even in direct sunlight. Enables clear visibility even when the viewer is wearing polarized sunglasses.



Specification subject to change | June 2022



Landscape & portrait

Both landscape and portrait orientations are possible, providing you with endless creative and functional possibilities to fulfil your commercial or informative goals.



178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees or visitors that will view Window Facing displays from diverse angles while passing by.



Smart Brightness Sensor

Adjusts the brightness of the monitor automatically according to the surrounding lighting conditions. This feature considerably reduces power consumption and increases the monitor's lifetime.



www.hisense-b2b.com



Hisense

Specifications

General		Special Order	
Model	75WF25	75WF35	75WF45
Screen Size	75"	75"	75"
Screen Active Area(mm)	1675.2x927.936	1675.2x927.936	1675.2x927.936
Resolution	UHD(3840x2160)	UHD(3840x2160)	UHD(3840x2160)
Aspect Ratio	16:9	16:9	16:9
Brightness(nit)	2500nits	3500nits	4500nits
Contrast Ratio	1200:1	1200:1	1200:1
Dynamic CR	Upto 250000:1	Upto 350000:1	Upto 450000:1
Viewing Angle(H/V)	178°/178°	178°/178°	178°/178°
Backlight Life Cycle	50,000 Hrs	50,000 Hrs	50,000 Hrs
Operation Hours	24/7	24/7	24/7
Response Time	8ms	8ms	8ms
Screen Orientation	Portrait or Land- scape	Portrait or Land- scape	Portrait or Land- scape

System

OS	Android 9.0
CPU	ARM Quad Core Cortex-A53 1.5G
GPU	Arm Mali-G52 2EE MC1
DDR	DDR 2GB
ROM	8GB EMMC
Language	Chinese/English

Connectivity

Input	USB2.0 x2, HDMI IN x2, Ethernet RJ45 x2, RS232 RJ45 x1, IR in x1, Sensor x1
Output	HDMI Out x1, Audio out x1

Network connection

Wifi or LAN	Yes			
3G/4G connection	Optional			
Speaker				
D.111	v			
Build in speaker	Yes			
Line-out Suppoert	Yes			
BT Speaker Support	Yes			
Thermal management				
Smart Backlight Control	Yes			
Smart Temperature Control	Yes			
Smart remperature control				
Smart Fans Control	Fanless			
Smart Monitoring System Cloud	Optional / CetusMSC			
Overheating protection	Yes			

75" High Brightness Display

Physical IP5X (Front Panel) IP rating Glass No Shell Aluminum Black Standard Color Bezel width(T/L/R/B) 15.3mm(T/B/L/R) 1682.66(H)x961.74(W)x56.75(D) mm Dimensions Net Weight TBD Packing Dimensions(W×H×D) 1797(W)x1076(H)x189(D) mm 20GP container capacity (pcs) 72 PCS 40GP container capacity (pcs) 144 PCS Operation Indoor window facing Working environment Auto Brightness control Light sensor Noise(Operating at 25±2°C,100cm apart from the module) - 10°c to 35°c (Direct Sunlight) - 10°c to 45°c (w/o Direct Sunlight) **Operation Temperature** (ambient temp.) 10% to 80% **Operation Humidity** Storage Temperature -10°c to +60°c Storage Humidity 10% to 80% Power AC 110 /220V,50/60Hz Power Supply Power Type Built-In Power Power Consumption TBD What's in the box Power cord Remote controller Accessories User manual WIFI antenna Dimensions **75**" 1682.66 x 961.74 x 56.75 mm TBD

www.hisense-b2b.com sales@hisense-b2b.com

HISENSE B2B EUROPE Beechavenue 139, 1119 RB Schiphol-Rijk,



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660