

# Pandora Nano 4GB Super

## Compact Edge AI

**YUAN**  
Visualize intelligent Planet

### Features

- Powered by NVIDIA™ Jetson Orin™ Nano 4GB Super up to 34 TOPS
- Compact Size: 145mm×123mm×66mm
- 4×M.2, 8 Lanes MIPI CSI-2, and I2C / UART / GPIO / CAN Bus
- 2×USB3.2 Gen2, 2×USB2.0, 1×Nano SIM Card Slot
- 1×HDMI1.4



### Specifications

System	
SOM Module	NVIDIA Jetson Orin™ Nano 4GB Super
CPU	6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3
GPU	512-Core NVIDIA Ampere Architecture GPU with 16 Tensor Cores
AI Performance	34 TOPS
System Memory	4GB 64-bit LPDDR5 51GB/s
Interface	
Storage	Supports External NVMe
Display Interface	1×HDMI1.4
Ethernet	2×RJ45 for 10/100/1000Mbps Ethernet DHCP Client
Expansion Slot	1×M.2 2280 M Key PCIe Gen3×2 Slot ( with Pre-Installed 128GB SSD ) 1×M.2 2280/3080 M Key PCIe Gen3×4 Slot, Support SSD or Video Capture Cards 1×M.2 2230 E Key PCIe Gen3×1+USB2.0 Slot, Support WiFi Module. 1×M.2 3042/3052 B Key USB3.2 Gen1 Slot, Support 5G/4G Wireless Module
USB	2×USB3.2 Gen2 ( Type-A ) 1×USB3.2 Gen2 ( Type-C ) ( OTG ) 2×USB2.0 ( Type-A )
MIPI	8-Lane MIPI CSI-2 ( D-PHY 2.1, Support MIPI Camera, Capture Card )
Audio	1×Line In ( 3.5mm Phone Jack ) 1×Line Out ( 3.5mm Phone Jack )
Peripheral Communication	40 Pin Header 1×I2S 2×I2C 2×SPI 1×UART 3×GPIO  14 Pin Header 1×CAN Bus 1×UART with CTS/RTS 1×UART for Debug
Misc. Features	1×Nano SIM Card Slot Firmware Upgradable TPM Module ( Optional )

### Video Encode / Decode


Video Feature	
Video Encode	NVIDIA Jetson Orin™ Nano Super: 1080p30 supported by 1-2 CPU cores
Video Decode	NVIDIA Jetson Orin™ Nano Super: AV1 ( Main Profile ) 1×4K60   2×4K30   5×1080p60   10×1080p30  H.265 ( Main, Main10 ) 1×4K60   2×4K30   5×1080p60   11×1080p30  H.264 ( Baseline, Main, High ) 1×4K30   3×1080p60   7×1080p30  VP9 ( Profile 0, Profile 2 ) 1×4K60   2×4K30   5×1080p60   11×1080p30

### Environment

Development Environment	
JetPack	6.2 or Higher
Environment	
Power Supply	DC input : 9~36V
Power Consumption	Max: 37.W
Operating Temperature	Standard Version: 0~60 °C with Airflow
Storage Temperature	-20~80 °C


### Mechanical

- Dimension of case: 145mm×123mm×66mm
- Dimension of main Board: 115mm×115mm
- Weight: 470g



## I/O Layout

- Carrier Board



\* All registered trademarks are the property of their owners. The photo is for reference only.

\* Technology License Patent Royalty. Supplier ( YUAN Technology Ltd. ) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.

Licensees or representatives such as MPEGLA, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660