

www.neousys-tech.com

PB-2500J Series

Industrial-Grade Intelligent Ultracapacitor-based Power Backup Module



✓ Key Features

- · Ultracapacitor-based, -25 to 65°C wide temperature operation
- · 2500 watt-second energy capacity
- · Up to 10 years lifetime and 500,000 charging/ discharging cycles
- · Patented CAP Sensing technology that
 - Maximizes back-up time in an event of unforeseen power outage
 - Monitors energy consumed and estimates the time required for system shutdown
- · Available in two form factors
 - A PCIe card for Neousys Nuvo-5000 and Nuvo-6000 series
 - A standalone module for other embedded computers

*R.O.C Patent No. 1598820

Introduction

Neousys' PB-2500J series is an innovative power backup solution for demanding industrial applications. Utilizing ultracapacitor technology, it features -25 to 65°C operating temperature range and extremely high durability. Compared to traditional battery-based UPS systems, PB-2500J series sustains superb reliability in extreme temperature environments and eliminates the drawback of battery performance degradation over time.

PB-2500J series is composed of eight 100F ultracapacitors to provide 2500 watt-second stored energy to sustain your computer during power outage and depending on your system's power consumption, it could be from seconds to minutes. But what makes PB-2500J novel is its patented CAP Sensing technology, an on-board processor that constantly monitors power consumption and evolves with the system. During a power outage, it maximizes the system operation time by estimating the perfect time to initiate system shutdown to prevent data loss.

PB-2500J series is available in two form-factors. PB-2500J-PCIe is a plug-and-play PCIe card specifically designed for Neousys' Nuvo-5000 and Nuvo-6000 series; and PB-2500J-CSM is a standalone module similar to UPS, it can be used for any embedded controllers with a DC input.

When it comes to industrial embedded controllers, stability and data loss prevention during power outages are just as important. Neousys' PB-2500J series aims to do the latter by redefining reliability and taking it to another level. With PB-2500J series, unexpected power loss and unstable power lines are a thing in the past!

Specifications

	_	
	PB-2500J-PCIe	PB-2500J-CSM
Ultracapacitor configuration	8x 100F, 2.7V ultracapacitors	
Capacity	2500 watt-second	
Lifetime	10 years @ 25°C at rated voltage* 1000 hours @ 65°C at rated voltage*	
Cycle life	500,000 charging/ discharging cycles*	
DC In	N/A	12 ~ 24 VDC via 3-pin terminal block
DC Out	N/A	12 VDC via 3-pin terminal block
Communication Interface	3-wire RS-232	
Dimension	Half-length PCIe card 167 mm (W) x 111 mm (H)	-
Mounting	N/A	DIN-rail mounting or wall-mounting
Operating Temperature	-25 ~ 65°C	
Storage Temperature	-40 ~ 70°C	
EMC	CE/FCC Class A, according to EN 55022 & EN 55024	

*Once the rated lifetime or cycle life has been reached, the capacity of ultracapacitor may decrease up to 30% and ESR may increase up to 100% from initial values.

Ordering Information

Model No.	Product Description	
PB-2500J-PCIe	Intelligent ultracapacitor-based power backup PCIe card with 2500 watt-second energy capacity	
PB-2500J-CSM	Intelligent ultracapacitor-based power backup standalone module with 2500 watt-second energy capacity	



All rights reserved. Copyright© 2017 Neousys Tech Inc.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660