

WTP-8865-12

12.1" Intel Atom Full IP65 Fanless Panel PC



Features

- Stainless steel enclosure
- True Fanless design for 0~40°C operation temperature
- Supports PCI Slot (Optional)
- Wide operating temperature range with smart fan solution
- Sun-light Readable Display with Low Reflection Touch Panel(Optional)
- Supports 802.11b/g Wireless Solution (Optional)
- User Friendly Button Control on Front Panel

System

CPU	Intel Atom N270 1.6Ghz
FSB	533MHz
Chipset	Intel® 945GSE chipset + ICH7M
BIOS	Award BIOS, ACPI supported
VGA	Intel Generation 3.5 integrated GFX Core(133 MHz) on board
Audio	Realtek ALC286 Audio Codec, 2+2 watts power amplifier
LAN	Marvell 88E8071 Gigabit Ethernet x 2
Memory	One DDR2 SODIMM socket supports up to 2GB
I/O	ICH7M
Serial ATA	Port x 1 with 150 MB/s transfer rate x 1
USB	7 USB 2.0 ports (External *4 ,internal*3)
COM	External x3, internal x2
WDT	Generates system reset; 256 segments

LCD Panel

Size	12.1"
Resolution (pixel)	SVGA (800x600)
Active Area (mm)	246.0 x 184.5
Pixel Pitch (mm)	0.3075x0.3075
Viewing Angle (H/V)	160/110
Brightness (cd/m²)	400
Contrast Ratio	500:1
Response Time (ms)	35
LCD Life Time (hrs)	50000

Touch Panel

Size	12.1"	12.1"
Type	5-wire	8 wire
	RES touch	Low reflection RES touch
Light Transmission	83%	74%
Mohs	3H	3H
Lifetime	35 million activations	2 million activations

Storage

HDD	2.5" SATA HDD drive bay x 1 (with anti-vibration mechanism)
CF	1 x bootable Compact Flash slot for CF type I/II storages (Optional CF card)
DOM	44PIN 180D x 1 (PCI card and DOM can't be in machine at the same time)

Expansion

On mother board

PCI x1	PCI slot x 1 (optional)
Mini-PCI	Mini-PCI-e X 1 socket

I/O Connectors

On mother board

VGA	DB-15 x 1
Audio Jack	Triple (3x1) phone jack connector (Line-in, Line-out, and Mic-in)
USB	USB 2.0 x4
COM	DB-9 x 3
KB/Mouse	PS/2 Connector x2 for keyboard/mouse
LAN	RJ45 x2 for Gigabit Ethernet

External I/O

USB	USB 2.0 x 2
COM	DB-9 x 2
KB/Mouse	PS/2 Connector x1 for keyboard/mouse
LAN	RJ45 x1 for Gigabit Ethernet

Power

Power	DC-In connector x 1
Front Bezel	Indicator/ Hot Key (Power Button/LCD Button/ brightness +/-)
Front LED color	Power: Green / Red: HDD accessing
Power Input	DC12V~28V
Power Adapter	AC 90 ~ 264V / 47 ~ 63 Hz / DC input 12V

Mechanical & Environmental

IP65/NEMA4 connectors x 7


Default: a.Power x1, b.USB x2, c.PS2 x1, d.COM x2, e.LAN x1
Customization : By request



WTP-8865-12

12.1" Intel Atom Full IP65 Fanless Panel PC

Drawing



Mechanical & Environmental

Construction	Stainless steel enclosure *SUS304 standard, SUS316 optional
Operation Temperature	0~40°C (Fanless)
	0°C ~50 °C (Fan) with wide temperature range storage
Storage Temperature	-30~85°C
Operation Relative Humidity	10%~90%, non-condensing
Storage Relative Humidity	10%~90%, non-condensing
Dimension	350x295x83.2 mm
Weight	7.2 kg
Mounting	VESA Mount 100/100
Shock	Operating: 15g/0.53 oz, 11 ms, half sine wave Non-operating: 50g/1.76 oz, 11 ms, half sine wave
Vibration	Operating: 5 ~ 17 Hz , Amplitude : 0.1", 17 ~ 500Hz , Acceleration : 1.0G
Drop test w/ packing	3 feet height free drop
Regulations	FCC-A, CE, VCCI, UL/cUL

Ordering information

1. WTP-8865-12 1.6G-512-160GB-SVGA
2. WTP-8865-12 1.6G-512-160GB-SVGA-L/R
3. WTP-8865-12 1.6G-512-8G SSD-SVGA – Wide Temp
4. WTP-8865-12 1.6G-512-8G SSD-SVGA-L/R –Wide Temp



Wincomm Corporation
3F, NO. 14, Prosperity Road II, Science-Based Industrial Park,
Hsinchu, Taiwan 30078, R.O.C
Tel : +886 3 578 0000 Fax: +886 3 578 0295

Web: www.wincomm.com.tw

Contact: sales_support@wincomm.com.tw

April 21, 2011

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660