

LMX-1202M-SFP Series

12-Port Industrial Gigabit Managed Ethernet Switch
w/8*10/100Tx, 2*10/100/1000Tx RJ45, and 2*100/1000 SFP Slots



Features


- ▶ Supports 8*10/100Tx Fast Ethernet Ports, 2*Gigabit 10/100/1000Tx RJ45 and 2*100/1000 SFP Slots for Fiber Connection
- ▶ Network Redundancy: STP/RSTP/MSTP, and G.8032 ERPS (Recovery Time <50ms)
- ▶ Supports IPv4/IPv6, and DHCP Option 66/67/82
- ▶ Supports Modbus/TCP Protocol for Device Management and Monitoring
- ▶ Configuration: Web Console, Telnet, CLI Command
- ▶ IGMP v1/v2/v3 for Multicast Traffic Filtering
- ▶ QoS (IEEE802.1p/1Q), CoS/ToS to Increase Determinism
- ▶ IEEE802.1Q VLAN for Easy Network Planning
- ▶ Enhanced Network Security with IEEE802.1X, SNMP v1/v2c/v3, HTTPS, and SSH/SSL
- ▶ Auto Warning by Exception through E-mail, Relay Output
- ▶ Support RMON Function for Efficient Network Monitoring
- ▶ Support Port Mirroring for Online Diagnostic
- ▶ 5-Year Warranty

INTRODUCTION

Antaira's LMX-1202M-SFP series is a 12-port industrial gigabit managed Ethernet switch that is embedded with 8*10/100Tx Fast Ethernet ports, 2*10/100/1000Tx RJ45, and 2*100/1000 dual rate SFP slots. This model is a fully manageable industrial Ethernet switch pre-loaded with standard Layer 2 network management software. The RJ45 ports provide flexibility to users for either 10/100 or 1000Tx Ethernet connections. The plug-in SFP modules provide 100MB or Gigabit Fiber connection where distance, EMI, or security is a concern.

The LMX-1202M-SFP series is compact, IP30 rated, and DIN-rail or wall mountable. There are also two wide operating temperature models for either a standard temperature range (STD: -10°C to 70°C) or an extended temperature range (EOT: -40°C to 75°C). It also provides high EFT and ESD protection for industrial networking applications; such as, power/utility, water wastewater, oil/gas/mining, factory automation, security surveillance, ITS, and any other outdoor or harsh environment.

DIMENSIONS



SPECIFICATIONS

Technology	
Standards	IEEE 802.3 10Tx Ethernet
	IEEE 802.3u 100Tx Fast Ethernet
	IEEE 802.3ab 1000Tx Gigabit Ethernet
	IEEE 802.3z Gigabit Fiber
	IEEE 802.3x Flow Control for Full Duplex
	IEEE 802.3ad for Port Trunk with LACP
	IEEE 802.1d STP (Spanning Tree Protocol)
	IEEE 802.1w RSTP (Rapid Spanning Tree Protocol)
	IEEE 802.1s MSTP (Multiple Spanning Tree Protocol)
	ITU-T G.8032/Y.1344 ERPS (Ethernet Ring Protection Switch) Protocol
Protocol	IEEE 802.1Q for VLAN Tagging
	IEEE 802.1x for Network Authentication
	IEEE 802.1p QoS/CoS Protocol for Traffic Prioritization
	IGMPv1/v2/v3, SNMPv1/v2c/v3, TFTP, SMTP, RMON, HTTP, HTTPS, Telnet, Syslog, DHCP Option 66/67/82, SSH/SSL, Modbus/TCP, LLDP, IPv4/IPv6, NAT, DHCP per port, SMTP, Quick ERPS, TLS
Switch Properties	
Switch Architecture	Back-Plane (Switching Fabric): 9.6Gbps
Configuration	Web Console, Telnet, CLI
Processing Type	Store and Forward
Flow Control	IEEE 802.3x for full duplex mode, back pressure for half duplex mode
Transfer Rate	14,880pps for 10Base-T Ethernet 148,800pps for 100Base-T Fast Ethernet 1,488,000pps for Gigabit Ethernet
Packet Buffer	4 Mbits
MAC Table Size	8K
VLAN Group	1 ~ 4094
IGMP Group	1024 Groups
Port Interface	
Ethernet RJ45 Port	8*10/100BaseTx auto negotiation, Full/Half duplex, and auto MDI/MDI-X connection
Gigabit Ports	2*RJ45 w/10/100/1000Tx and 2*100/1000 SFP Slots For Fiber
Wavelength	Refer to SFP Modules
RS232 Serial Console	1*RS232 in RJ45 connector with console cable, 115.2Kbps, 8,N,1
Configuration Backup	1*USB 2.0

Protection	
Overload Current	Present
Power Reverse Polarity	Present
CPU Watchdog	Present
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable; 100Base-TX: 2-pair UTP/STP Cat. 5 cable. EIA/TIA-568 100-ohm (100m)
	1000BaseTX: UTP/STP Cat.5/5E cable; EIA/TIA-568 100-ohm (100m)
Mechanical Characteristics	
LED Indicator	Per Unit: Power 1 & 2 (Green), Fault (Red)
Housing	Metal IP30 rated
Dimension	54 x 142 x 99 mm
Weight	Unit: 2.2 lbs.; Shipping: 3.3 lbs.
Mounting	DIN-Rail; Wall-Mount (optional)
Power Requirement	
Input Voltage	12~48VDC Redundant Input
Power Connection	1 removable 6-contact terminal block
Power Consumption	15 Watts
Environmental Limits	
Operating Temperature	STD: -10 to 70°C EOT: -40 to 75°C
Storage Temperature	-40°C ~ 85°C
Ambient Relative Humidity	5 to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Class A
EMS	IEC61000-4-2,3,4,5,6,8 IEC61000-6-2,4
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	FCC, CE, UL61010-1, 61010-2-201, NEMA TS2
Warranty	5 Years

ORDERING INFO

LMX-1202M-SFP	12-Port Industrial Gigabit Managed Ethernet Switch with 8*10/100Tx, 2*10/100/1000Tx RJ45 Ports, and 2*100/1000 SFP Slots
LMX-1202M-SFP-T	12-Port Industrial Gigabit Managed Ethernet Switch with 8*10/100Tx, 2*10/100/1000Tx RJ45 Ports, and 2*100/1000 SFP Slots; EOT: -40°C to 75°C
Optional Accessories	
SFP-M-T	1 Gigabit Fiber SFP Transceiver, Multi-Mode 550M / LC / 850nm, -40°C~85°C
SFP-S10-T	1 Gigabit Fiber SFP Transceiver, Single Mode 10KM / LC / 1310nm, -40°C~85°C
DIN-RACK-2U	Din-Rail to 19" Rack Mount Adapter for all Din-Rail Mountable Products, 2U Height

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660