

1-115P/R/G(H)	15" IP66 / IP69	K Stainless Steel Disp	lay		Industrial Panel PC	HMI Controller	Industrial Display Monitor
	 Every and the set of the set of						
				o o 324 229.09			
• • • • • • •	HDMI USB Speaker OSD Control	1 x W.F. HDMI with waterproof c 1 x M12 USB 2.0 with waterproo 1 x 2W IP65 speaker (option)					
	OSD on the rear side Membrane Power Connector 1 x M12 3-pin for DC power with waterproof cover and chain				Π	n	UNIT: mm Tolerance: ±0.5
	Display	Standard	High Brightness Optional				
	Display Type	15" TFT-LCD	15" TFT-LCD				
	Max. Resolution	1024 x 768	1024 x 768				
	Max. Color	16.2M / 262K 300	16.7M 1000				
	Luminance (cd/m ²) View Angle	176(H) /176(V)	160(H) /150(V)				
	Contrast	2000:1	800:1				
	Backlight Lifetime	70,000 hrs	50,000 hrs	Environmental Operating Tempe	rature 0~50°C / -20~60°C (optio	22)	
	5			Storage Tempera		jii)	
	Touch Screen			Humidity	10 to 95% @ 40°C, non-	condensing	
	Туре	Resistive Touch (for R model) Projected Capacitive Touch (for I Glass (for G model)	P model)	Certificate	CE/FCC Class A		
	Interface	USB		Ordering Inform	ation		
	Light Transmission(%)	Resistive Touch : 80% Projected Capacitive : 90%		VITAM-115P 1 F	5" XGA IP66/IP69K stainless steel disp rojected capacitive touch, 9~36V DC po	lay, VGA/HDMI input, OSD on the rear side, ower input with Adapter	
	Dever			ViTAM-115R	5" XGA IP66/IP69K stainless steel disp	lay, VGA/HDMI input, OSD on the rear side,	
	Power Power Input	DC 9~36V		STANFTISK 5	wire resistive touch window, 9~36V DC	C power input with Adapter	
	Power Consumption	VITAM-115R: Max 9W ViTAM-115PH: Max 17W		VITAM-115G 1	5" XGA IP66/IP69K stainless steel disp rotection glass, 9~36V DC power input	lay, VGA/HDMI input, OSD on the rear side, with Adapter	
	Mechanical	304 Stainless steel chassis(defa	ult), 316 Stainless steel	VITAM-115PH 1	5" XGA IP66/IP69K stainless steel disp rojected capacitive touch, 9~36V DC po	lay, VGA/HDMI input, OSD on the rear side, wer input with Adapter, 1,000 nits LCD	
	Construction Mounting	chassis(optional) VESA Mount 75 x 75, Yoke mou		VITAM-115RH	5" XGA IP66/IP69K stainless steel disp wire resistive touch window, 9~36V DC	lay, VGA/HDMI input, OSD on the rear side, c power input with Adapter, 1,000 nits LCD	
	IP Rating Dimensions	Total IP66/IP69K 399 x 324 x 53 mm		VITAM-115GH	5" XGA IP66/IP69K stainless steel disp rotection glass, 9~36V DC power input	lay, VGA/HDMI input, OSD on the rear side,	
	Net Weight	6.5 kg			I DIEGUOTI GIASS, 9~30 V DG POWER INPUT	with Auaptel, 1,000 fills LOD	

Industrial Panel PC

Industrial Panel PC



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660