

AVerCaster SE5810

1-CH HDMI/3G-SDI HEVC 1080p60 Compact Encoder





AVerCaster SE5810 is a single-channel video encoder allowing the independent Full HD video streams to be broadcasted or recorded at the same time. SE5810 takes HDMI or 3G-SDI video sources up to 1920 x 1080 Full HD resolution (maximum of 1920 x 1200, RB) and encodes a video stream of the same or various bitrates for broadcasting or recording. With powerful single H.265 high-profile codecs, SE5810 records live Full HD video at high quality for VoD playback, and simultaneously broadcasts it via popular streaming service providers such as Facebook Live to an unlimited number of viewers.

Features

- Support remote NAS storage or local storage to an external USB device/SD Card.
- Simultaneous streaming and recording up to 1080p60.
- Provide an audio out for monitoring purpose.
- Support preview function.
- Encode HEVC directly.
- Support PoE (Power over Ethernet).
- Provide physical buttons (stream, record and switch source) for intuitive operation.

Streaming and Recording Modes



Front and Rear View



Specifications

Video Interface	HDMI 1.4b x 1 3G-SDI x 1 Audio embedded
Audio Interface	3.5mm Line-in x 1 3.5mm Line-out x 1
Channels	1
Streaming or Recording Resolution	640 x 480 to 1920 x 1080, 1920 x 1200 (RB, reduced blanking)
Video Encoder	H.265, H.264
Audio Encoder	AAC
Recording File Format	MP4, MOV, TS
Protocol	TCP, UDP, RTMP, RTP, RTSP, RTMPS
Support Browser	Chrome
Support CDN	YouTube, Facebook Live
Preview Output	HDMI 1.4b
Streaming and Recording	1 to 1 Mode: 1 stream audio/video input, encode setting and same streaming protocol/recording.
	1, 1, 1 Mode: Simultaneous streaming and recording from the same video/audio source. Recording to network mapped drive from NAS and Windows shared folders.

Physical Buttons	Stream
	Record
Connectivity	Switch Source
	Ethernet x 1 RS-485
Storage	NAS
	USB 3.0 for local storage SD card slot for local storage
Power	Locking power supply 12V/5A; PoE (Power over Ethernet)
	Power adapter x 1
Accessory	Power cord x 1
	Quick guide x 1
Integration	API for integration and remote control via Web UI
Operating Environment	0° to +50° (+32° F to +122° F) Humidity: 0-80% RHNC
	-40° to +70° (-40° F to +158° F) Humidity: 0-90% RHNC
Storage Environment	-40° to +70° (-40° F to +158° F) Humidity: 0-90% RHNC
Dimensions (L x W x H)	213.5mm x 179.2mm x 41mm (8.41" x 7.56" x 1.61")
Weight	1131g (2.49lbs)

*All specifications are subject to change without prior notice.