

W22IK3S-SPA3

21.5" IP65 Flat Stainless PCAP Panel PC



KEY FEATURES

- 7th Generation (kaby Lake) Intel® Core™ i5-7200U 2.5GHz (turbo to 3.1GHz)
- A true flat, easy-to-clean front surface with edge-to-edge design
- Flat multi-touch panel pc with superior readability and P-Cap technology
- Plenty of I/O s including USB 2.0, RS232 serial port and RJ45-10/100/1000 LAN ports
- Sealed to IP65 for protection against water and dust
- Support Glove / Rain mode
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Various mounting solutions, Yoke mount and VESA mount
- Waterproof ports with adapter cables for external connectivity



SPECIFICATIONS

| Display | |
|------------------------------|--|
| Resolution | 1920x1080 |
| Contrast Ratio | 3000:1 |
| View Angles | 89,89,89,89 |
| Size | 21.5 inches |
| Panel Brightness | 250 nits |
| Touch / Glass | Projected Capacitive Multi Touch Screen |
| System Specification | |
| Processor | Intel® Core™ i5-7200U (3M Cache, up to 3.10 GHz) Intel® Core™ i5-7300U (3M Cache, up to 3.50 GHz) |
| Memory | 1 x SO-DIMM, DDR4 2133 MHz, 4GB 8GB (Optional) 16GB (Optional) |
| Storage | 1 x M.2 2242 SSD 64GB M.2 2242 SSD up to 512GB (Optional) |
| Ethernet controller | Intel® Ethernet Controller I211-AT + Intel® Ethernet Connection I219-LM |
| Security | TPM 2.0 |
| Operating System | Windows 10 IoT Enterprise (Optional) Linux Ubuntu 18.04 (Optional) |
| WLAN | 802.11 a/b/g/n/ac (Optional) |
| BT | BT Support (Optional) |
| Mechanical | |
| Dimension | 541 x 337 x 56.2 mm |
| Mounting | VESA Mount Yoke Mount |
| Enclosure | Stainless Housing |
| Cooling System | Fanless design |
| Environment | |
| Operating Humidity | 10% to 90% (non-condensing) |
| Operating Temperature | 0~45°C |
| Storage Temperature | -20~60°C |
| IP rating | IP65 |
| Certification | |
| Certification | CE, FCC |
| IO Ports | |
| USB Port | 1x M12 waterproof connector for 2 x USB2.0 |
| Serial Port | 1 x M12 waterproof connector for RS232 |
| LAN | 1 x waterproof Giga LAN RJ45 connector |
| Indicator | 1 x LED Indicator for power 1 x LED Indicator for storage |
| Control | |

| | |
|---------------|--------------------------------------|
| Button | 1 x Power Button 1 x Reset Button |
|---------------|--------------------------------------|


Accessory

| | |
|------------------|---|
| Accessory | 100~240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps Driver CD & Manual VESA screws |
|------------------|---|

Power

| | |
|---------------------|-------------------|
| Power Rating | 12V DC (M12 type) |
|---------------------|-------------------|

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
3. All specifications are subject to change without prior notice.