

EZMaker SDK Express (C725B)



Actual product image may vary from image shown.



- E-learning projection and presentation capture
- Surveillance system A/V feeds backup
- Video conferencing capture and backup

Features

- Fully DirectShow compatible
- Support uncompressed video capture in AVI or WMV format
- Support snapshot in BMP or JPG format
- Capture and digitalize NTSC/PAL/SECAM analog signals
- Support multiple programming languages

Support Software

- Microsoft DirectShow
- UStream Producer
- Adobe Flash Media Live Encoder 3
- Microsoft Windows Media Encoder 9
- Microsoft Express Encoder
- Real Producer(v13)
- CyberLink PowerDirector/PowerProducer
- GraphEdit
- AMCap
- XSplit
- Telestream Wirecast
- Corel VideoStudio

Specifications

| | |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Input | S-Video, Composite video |
| Audio Input | RCA audio |
| Video Resolution | 160×120 / 176×144 / 240×180 / 240×176 320×240 / 352×240 / 352×288 (PAL only) 640×240 / 640×288 / 640×480 704×576 (PAL only) / 720×240 / 720×288 720×480 / 720×576 (PAL only) |
| Pixel Format | YUY2(4:2:2), UYVY (4:2:2), RGB24 (4:4:4) |
| Color Adjustment | Brightness, Contrast, Hue, Saturation, Sharpness |
| Multi-Card Support | Yes (up to 8 cards) |
| Programming Language | VC, VB, Delphi, C#, VB.NET |
| SDK Framework | General DLL |
| Operating Environment | Temperature: 0 to 65°C Humidity: 15 to 80% RHNC |
| Storage Environment | Temperature: -30 to 65°C Humidity: 15 to 90% RHNC |
| Power Requirement | 3.3V max 400mA |
| Dimensions (mm) | 93.5(L)*68.78(W)*1.57(H) |

System Requirements

- **CPU**
 - Intel® Pentium® 4 3.0 GHz
 - AMD Athlon™ 64 3200+
- **VGA card with support for DirectX9.0c or above**
- **512 MB RAM**
- **PCI-E Slot**
- **Sound Card**
- **Windows® 8/7/XP (32/64-Bit)**