



VT-FORS GOLD TRACTOR ONLY

Bespoke kit built specifically for tractor units.

THIS KIT INCLUDES THE FOLLOWING:

1. **VT5500-G-1TB**
5CH MDVR
Includes 1TB Hard-drive



2. **VT-C20-MINI****
Forward-facing Camera



3. **VT-LT ALERT**
Left-turn Alert



4. **VT-CAN-M8***
Side Scan Interface
(Vehicle 2012 or newer)



5. **VT-WNREVERSINGALARM**
White Noise
Reversing Alarm



6. **VT-TIMER CUT OUT**
Timer cut-out button



7. **VT-M4-7-AHD (Kit)**
4CH AHD Monitor
Includes 5M Cable, F2F Convertor, Brackets



8. **VT408-AHD x2**
HD Side-View Camera



9. **VT408 Spacer 50mm x2**
VT408 Spacer 25mm x2



10. **VT-SIDE SCAN**
VT-Sensor Brain (No Sensors)
VT-Sensor Display + Mixture of x4 sensors



11. **VT-CORNER SCAN**
VT-Sensor Brain (No Sensors)
VT-Sensor Display + x4 flush sensors



12. **VT646-AHD****
Rear-view
Camera



13. **VT-SUZI COIL**
Cable for Trailer
Camera



14. **VT-C5M x3**
VT-C15M x1



15. **VT-SUZI TRACTOR ONLY**
Suzi Input



16. **VT-C-MALE TO FEMALE**
Camera input splitter
for camera



17. **VT-IMAGE SPLITTER (AUTO)**
Auto Image
Splitter



KEY FEATURES:

VT5500-G

- Supports 4 channels AHD (1080P) +1 channel IPC (1080P)
- Supports hard disk for main recording
- Alarm integration for central monitoring
- Supports GPS and 3G/4G
- Built-in three-axis inertial sensor
- Vibration-resistant design



VT-LT ALERT

- Dual voltage 12-24 volts
- Bracket Mounted (2 Bolt Fixing)
- M.I.R.A. tested for all on and off road applications
- CE and emc marked
- Epoxy sealed for greater durability against water and vibration
- Pressure washable – IP6



VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated - sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm



VT408-AHD

- DC 12V~24V
- 120°
- 62(L) x 44(H) x 62(W) (mm)
- 20°C + 70°C
- 1280 x 720 pixels



VT-SIDE SCAN

- 4 sensors mixed sensors
- PCB built into sensors
- Splash-proof ECU
- Digital distance display w/buzzer
- DSM scanning technology
- Dual voltage

VT-CORNER SCAN

- 4 Flush sensors
- PCB built into sensors
- Splash-proof ECU
- Digital distance display w/buzzer
- DSM scanning technology
- Dual voltage

VT-C20-MINI

- 1/2.8" SONY 2.13-megapixel
- 1920 x 1080 resolution
- 0.05 Lux/F1.2 (Auto Gain on)
- 3.6mm
- DC 12V±10%
- 90(L) x 46(H) x 70(W)mm



VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable – IP67
- 2 Wire



VT-M4-7-AHD (Kit)

- 10.1-inch digital screen
- Resolution 1024 x 600p
- 4 video inputs and 4 trigger wires
- Power voltage of DC10V~36V
- 352(L) x 166(W) x 32(D) mm



VT408 Spacer 50mm

- 65(L) x 50(H) x 55(W) (mm)



VT408 Spacer 25mm

- 65(L) x 25(H) x 55(W) (mm)



VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle)
- IR night vision
- 50(L) x 50(H) x 80(W)mm



VT-WARNING STICKER BLIND SPOT



*Additional charges may be involved.
 **Not required for FOR5 but VisionTrack recommend.
 For more information please go to www.visiontrack.com

