



# VT-FORS SILVER ARTIC

Bespoke kit designed specifically for artic vehicle types

## THIS KIT INCLUDES THE FOLLOWING:

**1. VT-SIDE SCAN**

VT-Sensor Brain (No Sensors)  
VT-Sensor Display + Mixture of 4 x sensors



**2. VT-CORNER SCAN**

VT-Sensor Brain (No Sensors)  
VT-Sensor Display + 4 x flush sensors



**3. VT-LT ALERT**

4 Wire  
Left-turn Alert



**4. VT-CAN-M8\***

Side Scan Interface  
(Vehicle 2012 or newer)



**5. VT-WNREVERSINGALARM**

White Noise  
Reversing Alarm



**6. VT-TIMER CUT OUT**

Timer cut-out button



**7. VT-M4-7-AHD (Kit)**

4CH AHD Monitor  
Includes 5M Cable, F2F Converter, Brackets



**8. VT408-AHD**

HD Side-View Camera



**9. VT408 Spacer 50mm x1  
VT408 Spacer 25mm x1**



**10. VT646-AHD\*\***

Rear-view  
Camera



**11. VT-C10M**

10 Metre Cable



**12. VT-WARNING STICKER  
BLIND SPOT  
Vehicle Signage**



Product specifications can be found on the next page of this documents.

\* additional charge may be involved.

\*\*Not required for FORS but VisionTrack recommend.

## KEY FEATURES:

### VT-SIDE SCAN

- 4 sensors mixed sensors (Flush/Non-Flush)
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage



### VT-CORNER SCAN

- 4 Flush sensors installed using holes
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage



### VT-LT ALERT

- Dual voltage 12-24 volts
- Bracket Mounted (2 Bolt Fixing)
- M.I.R.A. tested for all on and off road applications
- CE and emc marked
- Epoxy sealed for greater durability against water and vibration
- Pressure washable – IP6



### VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable – IP67
- 2 Wire



### VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated - sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm



### VT-M4-7-AHD (Kit)

- 10.1-inch digital screen
- Resolution 1024 x 600p
- 4 video inputs and 4 trigger wires
- Power voltage of DC10V~36V
- 352(L) x 166(W) x 32(D) mm



### VT408-AHD

- DC 12V~24V
- 120° wide-viewing angle
- 62(L) x 44(H) x 62(W) (mm)
- -20°C + 70°C
- 1280 x 720 pixels



### VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle
- IR night vision
- 50(L) x 50(H) x 80(W)mm



### VT408 Spacer 50mm

- 65(L) x 50(H) x 55(W) (mm)



### VT408 Spacer 25mm

- 65(L) x 25(H) x 55(W) (mm)



### VT-WARNING STICKER BLIND SPOT



For more information please go to [www.visiontrack.com](http://www.visiontrack.com)

