











Intel® Atom processor

9.7" indoor/outdoor LCD

barcode scanner

magstripe

color camera

debit pin pad

GPS, WLAN, WWAN, WPAN



# • Other Benefits to Servicing the Retail Customer: Immediate access to products, pricing, & inventory allowing for real-time customer centric selling. On demand creation of virtual customized products. Instant completion of customer satisfaction surveys & loyalty card processing. Improved customer recognition. Creation and deployment of return

# • Other Features of the DLI 9000 Rugged Tablet: Cellular voice and data capabilities. Dual integrated

color cameras. Intel® Atom processor with 2GB of memory and 64GB of storage. Fully integrated WiFi, GPS, CDMA/GPRS and Bluetooth radios.

# • Other Benefits of DLI:

counters and POS kiosks.

Comprehensive Implementation Services. Customized OS Image Support. Custom Tailored Service Plans.



# Finally. **Five Powerful Payment Features.** One Talented Machine.

Retailers have strived to improve the customer experience for years... DLI listened. Our exclusive 5-in-1 payment module is an evolutionary design offering five features for full service payment processing. The module's state of the art design leaves no sale incomplete. This 5-in-1 payment module includes a magstripe, debit pin pad, contactless payment (NFC™), EMV™, and barcode scanning. The DLI 9000 rugged tablet is the perfect solution to capture the customer & complete the sale.

This rugged tablet empowers you to deliver immediate customer facing solutions resulting in increased sales whether you are collecting table side orders, line busting, or providing roaming customer service. The DLI 9000 rugged tablet serves as a portable management tool by allowing direct & immediate access to your CRM and ERP. Built on common PC architecture, the DLI 9000 rugged tablet allows for increased flexibility in the management & maintenance of both OS images (Windows® or Android®) and OPOS/JPOS compliant drivers.

Housed in an impact-resistant IP54 enclosure, DLI has successfully merged the industrial requirements of a rugged tablet with the sleek design desired by the retail market revolutionizing the tablet industry. Its lightweight design, weighing in at less than two pounds, and large industrial rated 9.7" indoor/outdoor LCD touchscreen, allows you to easily go to the customer with full portable payment processing. The DLI 9000 rugged tablet offers your customer a secure & convenient way to pay with a PCI compliant debit pin pad and integrated TPM chip set.

The DLI 9000 rugged tablet delivers the flexibility, reliability and return on investment that today's retail operations demand. Contact DLI today for more information at: (800) 526-1299.











dust v

Intel® Atom Processor • 9.7" indoor/outdoor LCD • GPS

Barcode Scanner • Magstripe • Color Camera • RFID

Debit Pin Pad • WLAN • WWAN • WPAN

### **System**

- Casing Impact-resistant ABS+PC polymer, IP54 rated, multiple 4ft drops to bare concrete
- Processor Intel® Atom Z670 1.5GHz
- Chipset Intel® SM35 Express, L2 Cache: 512KB
- **Display** 9.7" (1024 X 768) Contrast Ratio: 800:1
  - 400NIT LED Backlit indoor/outdoor readable
- Touchscreen Projective Capacitive
- Video 256MB
- Audio Intel High Definition Audio; dual integrated speakers
- Memory 2GB DDR2 800Mhz
- Storage SATA Micro SSD 64GB
- **Security** Trusted Platform Module (TPM 1.2)
- Operating System Windows® 7 Pro/Ultimate, Windows® Embedded 7, Windows® Embedded POSReady 7, Android® 4.0 ICS
- **Ports** (1) USB 2.0, (1) HDMI, (2) I/O Pass through connections to the cradle, (2) RF Pass though connections to the cradle
- Barcode Scanner Integrated CMOS 1D/2D Imager (OPOS/JPOS Compliant) (Optional 5-in-1 Module)
- Magstripe Reader Integrated 3 track encrypted sensor, Single head (OPOS/JPOS Compliant) (Optional 5-in-1 Module)
- **RFID** Integrated reader ISO 14443 with SAM Support (OPOS/JPOS Compliant) (Optional 5-in-1 Module) \*Supports NFC<sup>TM</sup> & Contactless Payment
- EMV<sup>™</sup> Smartcard Reader Integrated EMV<sup>™</sup> ISO/IEC 7816 contact reader (OPOS/JPOS Compliant and supporting Direct IO commands) (Optional 5-in-1 Module)
- Debit Pin Pad Integrated PCI Certified Debit Pin Pad (OPOS/JPOS Compliant and supporting Direct IO commands) (Optional 5-in-1 Module)
- **Keys** (4) Programmable keys, (1) Power on/off key, (1) Battery Status key, (2) Camera/Barcode Scanner keys (L & R side)

### **Environmental**

- **Temperature** Operating 0°F to +122°F (-17°C to 50°C) - Storage -4°F to +149° (-20°C to 65°C)
- Impact Multiple 4' drops to bare concrete
- Vibration 5-500Hz 1G PTP
- **Shock** Operating -20G (11ms); Non Operating -40G (11ms) Crash -50G (11ms)
- EMI/EMC FCC Class B, CE
- Water/Dust IP54; Dust (Protected against dust limited ingress), Water - (Protected against sprays from all directions - limited ingress)

### **Physical**

- **Dimensions** H–8.11" (206mm), W–10.35" (263mm), D-0.60" (15.4mm)
- Weight 2lbs 11oz (with battery pack & 5 in 1 Module)
- Warranty Standard One Year. Available No-Fault Service Coverage
- GPS ublox 6 chipset with Internal Active Patch Antenna
- Camera Color, (1) Forward facing 1.3MP, (1) Rear facing 2MP w/flash
- WiFi 802.11 a/b/g/n WiFi Radio (Cisco® CCX4)
- **WWAN** Integrated Gobi3000™ GPRS/CDMA Cellular Card (optional) available cellular carriers: Verizon®, AT&T®, T Mobile®
- **Bluetooth** Class 2 Radio
- **Voice Communications** Integrated microphone, Integrated 3.5mm headset/mic jack
- Ambient Light Sensor Integrated control via EC & OS
- **Power** Battery Pack: 4000mAh Lithium Ion Battery (6hrs of usage @ level 7 brightness) \*Wifi, Bluetooth enabled
- AC Adapter 19VDC 65Watt 110/220 VAC 50/60 Hz Input, multicountry line cords available

### Accessories

- **Desktop Cradle** Port replicator, (3) USB, (1) Ethernet 10/100, (1) VGA, (1) K-Lock
- **Vehicle Cradle** Power filtering 10v-60v Input, Port replicator, (3) USB, (1) Ethernet 10/100, (1) RS232, External Cellular, WiFi and GPS antenna passive connections, (2) RF Pass through connections, (1) K-Lock
- **7-Bay Ethernet Cradle** 7 bay unit charging cradle with Ethernet 10/100 switch

Information in this document is subject to change without notice.











