



IPPC 1560TP2E-DC



IPPC 1560TP2E-AC



IPPC 1560TE

Main Features

- 4:3 15" XGA Fanless Panel Computer
- Powerful 2nd/3rd generation Intel® Core™ processor
- Two expansion slots for add-on PCI or/and PCIe cards
- Optional 3.5G/Wi-Fi module/2.5" HDD/3 x Coms/GPIO/DIO/Dimming Control Button
- Front accessible USB2.0 for easy of field maintenance
- Metal housing with robust aluminum front bezel for harsh environment
- IP65 compliant front panel
- Support fieldbus module, JMobile HMI, Citect SCADA and CODESYS SoftLogic (optional)
- Optional: wide range DC power input model/isolation protection DC power input model

Product Overview

IPPC 1560T is a heavy industrial panel PC equipped with powerful 2nd/3rd generation Intel® Core™ processor, TFT LCD panel with LED backlight and user-friendly touch screen. It provides two expansion slots to support PROFINET, PROFIBUS, DeviceNet, EtherNet/IP and EtherCAT protocols. The NEMA4/IP66 rated heavy-duty aluminum front bezel and the vibration-resistant rugged chassis are specifically designed for outdoor and harsh industrial environments. IPPC 1560T is ideal for use in oil and gas rig, wind farms, chemical factories, pharmaceutical factories, and hazardous working area.

Specifications

System

- CPU: Support 2nd/3rd gen. Intel® Core™ processor family, rPGA 988
 - Intel® Core™ i7-3520ME (2 x 2.9GHz, 4M cache, Max. TDP 35W)
 - Intel® Core™ i5-3610ME (2 x 2.7GHz, 3M cache, Max. TDP 35W) (Default)
 - Intel® Core™ i3-3120ME (2 x 2.4GHz, 3M cache, Max. TDP 35W)
 - Intel® Celeron® B810 (2 x 1.6GHz, 2M cache, Max. TDP 35W)
 - Intel® Pentium® B950 (2 x 2.1GHz, 2M cache, Max. TDP 35W)
- BIOS: AMI BIOS
- System chipset: Intel® HM76 Express chipset
- System memory: 1 x 204-pin DDR3 SO-DIMM socket, 4G DDR3 (Default), support up to 8GB DDR3-1066/1333, non-ECC and un-buffered
- Storage device:
 - 1 x external locked CFast socket
 - 2 x hard drive bay: optional 2 x 2.5" SATA HDD
- Watchdog timer: Watchdog timeout can be programmable by software from 1 second to 255 seconds and from 1 minute to 255 minutes (Tolerance 15% under room temperature 25°C)
- H/W status monitor: monitoring system temperature, and voltage
- Expansion:
 - 2 x Mini-PCIe sockets (support optional Wi-Fi or 3.5G module)
 - 2 x expansion slots for add-on PCI or/and PCIe cards
 - 1 x PCI and 1 x PCIe4 slots (Default)
 - 2 x PCIe4 slots
 - 2 x PCI slots
- Panel backlight control button: increase brightness/decrease brightness/backlight on/off (for IPPC 1560TP2E-AC only)

Rear I/O

For All

- 2 x PS2 keyboard/mouse
- 2nd display VGA port: 1 x DB15
- Ethernet: 2 x RJ45

For IPPC 1560TP2E-DC only

- USB: 5 x USB2.0 (1 in front)
- Audio port: 1 x Line-out; 1 x Line-in; 1 x MIC-in
- COM #1: RS232/422/485 w/ RI or 5V or 12V selection
- COM #2: RS232/422/485 w/ RI or 5V or 12V selection
- COM #3: RS232 w/ RI or 5V or 12V selection
- ATX power switch
- Reset button


For IPPC 1560TP2E-AC only

- USB: 5 x USB2.0 (1 in front)
- Audio port: 1 x Line-out; 1 x Line-in; 1 x MIC-in
- COM #1: RS232/422/485 w/ 2.5kv isolated protection
- COM #2: RS232/422/485 w/ 2.5kv isolated protection
- COM #3: RS232 w/ RI or 5V or 12V selection
- COM #4: RS232 w/ RI or 5V or 12V selection
- COM #5: RS232
- COM #6: RS232
- DIO w/ 2.5kv isolated protection:
 - 4 x Digital Input (Source type)
 - 4 x Digital Output (Sink type)
- GPIO: 4 x digital in/4 x digital out
- LPT: Parallel port
- AC Power switch
- Reset button

For IPPC 1560TE only

- USB: 4 x USB2.0 (Hidden)

Dimension Drawing



- COM #1: RS232/422/485 w/ 2.5kv isolated protection
- COM #2: RS232/422/485 w/ 2.5kv isolated protection
- COM #3: RS232 w/ RI or 5V or 12V selection
- ATX Power switch
- Reset button

Audio

- AC97 codec: Realtek ALC886-GR
- Audio interface: Line-out/Line-in/MIC-in audio Jack

Ethernet

- LAN chip: dual Intel® 82574L Gigabit LAN
- Ethernet interface: 10/100/1000 Based-Tx Ethernet compatible

Fieldbus

- IPPC 1560TP2E-DC/IPPC 1560TE: support up to two fieldbus module (1 universal kit and 1 special kit)
- IPPC 1560TP2E-AC: support one special fieldbus module kit

Mechanical & Environment

- Color: pantone 432C\RAL 70 24 front bezel
- Enclosure: aluminum front bezel with SPCC nickel plated housing
- IP protection: IP65 front
- Mounting: panel/wall/stand/VESA 100mm x 100mm
- Power

For IPPC 1560TP2E-DC

- Power Input: +9 to 30VDC
- Power Adapter: optional AC to DC DIN rail power adapter (+24V, 120W)

For IPPC 1560TP2E-AC

- Power input: 100-240V~, 1.5A, 50-60Hz; fuse: 250VAC/3A
- Power connector: AC inlet (IEC60320 C14)
- Power supply: 120W

For IPPC 1560TE

- Power input: +24V DC+20% with 1.5kv isolated protection
- Fuse: 250V/10A

Vibration:

- IEC 68 2-64 (w/ HDD)
- 1Grms @ sine, 5~500Hz, 1hr/axis (HDD operating)
- 2Grms @ sine, 5~500Hz, 1hr/axis (CFast operating)
- 2.2Grms @ random condition, 5~500Hz, 0.5hr/axis (non-operating)

Shock:

- IEC 68 2-27
- HDD: 20G @ wall mount, half sine, 11ms

- Operating temperature: -10°C to 50°C
 - * Intel® Core™ i7/Intel® Celeron® B810/Intel® Pentium® B950: -10°C to 40°C
- Storage temperature: -20°C to 75°C
- Operating humidity: 10%~90% relative humidity, non-condensing
Limits to be at 90% RH at max 50°C

Certifications

- CE (including EN61000-6-2/EN61000-6-4)
- FCC Class A

Ordering Information

System

- **IPPC 1560TP2E-DC (P/N: 10I11560T00X0)**
15" XGA LED backlight fanless touch panel PC, Intel® Core™ i5-3610ME 2.7GHz, touch screen, 4GB DDR3, 3 x COMs, DC power input
- **IPPC 1560TP2E-AC (P/N: 10I11560T01X0)**
15" XGA LED backlight fanless Touch panel PC, Intel® Core™ i5-3610ME 2.7GHz, touch screen, 4GB DDR3, 6 x COMs, 4 x 4GPIO, 4 x 4DIO with isolated protection, AC power input
- **IPPC 1560TE (P/N: 10I11560T02X0)**
15" XGA LED backlight fanless touch panel PC, Intel® Core™ i5-3610ME 2.7GHz, touch screen, 4GB DDR3, 3 x COMs, isolated protection DC Power

Optional

- **24V/5A, 120W AC to DC DIN rail power adapter w/ o power cord (P/N: 7440120001X00) (for IPPC 1560TP2E-DC and IPPC 1560TE)**
- **Riser card 2 x PCI slots (P/N: 20JK036P200X0)**
- **Riser card 2 x PCIe4 slots (P/N: 20JK036E200X2)**
- **Fieldbus module universal kit (for IPPC 1560TP2E-DC and IPPC 1560TE)**

88J50090E00X0	FBI 90E-PNM kit (w/ 25 cm cable)	PROFINET master
88J50090E01X0	FBI 90E-EP kit (w/ 25 cm cable)	EtherNet/IP master
88J50090E02X0	FBI 90E-ECM kit (w/ 25 cm cable)	EtherCAT master
88J50090E03X0	FBI 90E-PBM kit (w/ 25 cm cable)	PROFIBUS master
88J50090E04X0	FBI 90E-DNM kit (w/ 25 cm cable)	DeviceNET master