





LA Series Wide Temperature Sunlight Readable Full IP65 Monitor




-  Touch Function
-  Waterproof Design
-  Housing Design
-  OSD Controller
-  Heat/cold-resistant
-  Sunlight Readable
-  IP65 chassis, IP65 connectors, IP65 power adapter (alternative)
- Stainless steel**
- Rear side**
- 20°C ~ 55°C**
- Up to 1600 nit**

Power Supply	Standard / IP65-rated DC in 12V (default) or DC in 19V ~ 36V (optional) external power adapter
I/O Ports (Default)	1 x VGA, 1 x USB or RS232 for resistive touch screen
Op. Temp. for Monitor	-20°C ~ 55°C
Op. Temp. for Adapter	-20°C ~ 50°C
Storage Temperature	-25°C ~ 70°C
Relative Humidity	0% ~ 95% non-condensing
OS Support	Win 7 Pro, Embedded 7, Win XP Pro, Embedded XP
Installation	VESA mount 100 x 100 mm
Optional Items	None touch screen

Model Name	12V	LA-ZJL15RF			LA-ZJL17RF
	19~36V	LA-ZJL15RW			LA-ZJL17RW
Display	Size / Aspect Ratio	15" TFT (4:3)			17" TFT (4:3)
	Backlight	LED			LED
	Resolution	1024 x 768			1280 x 1024
	Colors	16.7 M	16.2 M	16.7 M	16.7 M
	Luminance (cd/m ²)	1600	1000	800	1600
	Contrast Ratio	700:1	700:1	700:1	1000:1
	Viewing Angle (H/V°)	160/160	160/160	160/160	170/160
	MTBF (hrs)	70,000			70,000
Touch Screen	5-wire resistive			5-wire resistive	
Dimension (W x H x D, mm)	380 x 290 x 67			425 x 361 x 68	
Weight (kg)	8			9	
I/O port's position	Bottom			Rear	
OSD Controller	Yes (rear)			Yes (rear)	

Highlights



Hairy brushed finish
to deliver an aesthetic appearance

SA / HA / DA / LA / TA / UA / EA / VA Series