

# PM3205-QF35L0

## Specification

Panel Mount, 32" LCD monitor, 3840 x 2160, LED 350 nits, 1 x VGA + 5 x HDMI + 1 x DP input



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |   |   |   |
|---------------------|---|---|---|
| Panel               | Cell Type / Glass Surface   | TFT LCD / Black Anti-Glare, low reflection coating          |   |
|                     | Aspect Ratio / Size   | Wide / 32" viewable diagonal area                           |   |
|                     | Active Area / Pixel Pitch   | 698.4(H) x 392.85(V) mm / 0.181(H) x 0.181(V) mm            |   |
|                     | Native Resolution / Colors  | 3840(H) x 2160(V) / 1.073B                                  |   |
|                     | Brightness / Contrast   | 350 cd/m <sup>2</sup> (typ) / 3000 : 1                      |   |
|                     | Response Time   | ≤ 9.5 ms (G-to-G)   |   |
|                     | Viewing Angle (typical)   | H.178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)             |   |
|                     | Light Source  | LED backlight, Long life, 35,000 hrs (typ)                  |   |
| Input Sources       | PC System   | Signal  | Analog RGB (0.7/1.0 V <sub>pp</sub> , 75 ohms)          |
|                     |   | Sync  | Separate Sync, Composite Sync, Sync On Green            |
|                     |   | Frequency   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System  | 2W speaker x 2  |   |
| Input Terminals     | 1 x VGA , 5 x HDMI, 1 x DP , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |   |   |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)            |   |   |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)     |   |   |
| Power               | Internal power supply with universal / Auto-Sensing, AC90 to 260V, 50/60 Hz           |   |   |
| Power Consumption   | Operation / Power Saving  | 73.75 watt , < 1 watt (Support DPMS)                        |   |
| Operating Condition | Temperature / Humidity  | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |   |
| Storage Condition   | Temperature / Humidity  | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |   |
| Certification       |   | FCC , CE  |   |
| Dimensions          | Physical  | Please refer to Drawing                                     |   |
|                     | Carton  | W x H x D = TBD   |   |
| Weight              | N.W. / G.W.   | 14.5 Kgs / 16 Kgs   |   |
| Container Loaded    | 20ft / 40ft / 40ft HQ   | TBD (Sets , By pallet)                                      |   |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |