


# CAB-201



## Spotlight Features

- Supports PICO-ITX module
- 1 x DisplayPort
- 1 x USB 3.0, 1 x USB 2.0, 2 x SATA3
- 1 x PCIe
- 1 x mini-PCIe
- 1 x M.2(Key E)
- 1 x MIOe
- DC 12V DC-in

## Specifications

### Processor System

Dimension	Micro ATX ( 9.6-in x 6.7-in ) / ( 244 mm x 170 mm )
CPU	By CPU Board
Chipset	By CPU Board

### Expansion Slot

PCIe	1 x PCIe x1
Mini PCIe	1x full size(Mini PCIe only )
M.2	1 x M.2 Slot (Key E), supports type 2230 for WiFi + BT Module
mSATA	N/A
MIOe	HDMI or DP , 3 x USB2.0 or 1 x USB3.0 + 1 x USB2.0 , 4 x PCIe x1 , LPC bus , SMBus

### Memory

Technology	By CPU Board
Max.	By CPU Board
Socket	N/A

### Graphics

Controller	By CPU Board
VGA	N/A
LVDS	N/A
HDMI	N/A
DVI	N/A
DisplayPort	Supports max resolution up to 4096 x 2160@60Hz
Multi Display	By CPU Board

### Ethernet

Interface	By CPU Board
Controller	By CPU Board
Connector	By CPU Board

### Rear I/O

VGA	N/A
DVI	N/A
HDMI	N/A
DisplayPort	1
Ethernet	N/A
USB	1 x USB3.0 , 1 x USB2.0
Audio	N/A
Serial	N/A
PS/2	N/A

### Internal Connector

USB	1 x USB 2.0
LVDS	N/A
eDP	N/A
VGA	N/A
Serial	N/A
SATA	N/A
Parallel	N/A
GPIO	N/A
SATA PWR Output Con	N/A
Speaker Header	1
TPM	N/A

### Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 segments, 0,1,2...255sec/min

### Power Requirements

Input PWR	12V DC-in
Power On	AT/ATX Supported AT : Directly PWR on as power input ready ATX : Press button to PWR on after power input ready

### Environment

Operating Temperature	0°C – 60°C
Storage Temperature	-40°C – 85°C