
## **DK SERIES**


## DK751DR5

75" 4000 nits 4K UHD Dual-Sided Ultra-High Brightness Outdoor Kiosk





LOW POWER CONSUMPTION




SUNLIGHT VIEWABLE IMAGE

LCD Panel Size



VANDAL RESISTANT



VIEWABLE WITH POLARIZED LENSES



WEATHER PROOF

74.52" (x2)

	Native Resolution	3840 x 2160
	Brightness	4000 nits
PANEL	Color Depth	10 bits
	Contrast Ratio	3000:1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)

Power Supply Internal 200-240V ~ 50/60HZ Power Consumption (Typ./ Max.) 930 W / 2100 W [Basic]

MECHANICAL SPECS	Bezel Width (T/B/L/R)  Monitor Dimension (LxHxD)  Monitor Weight	117.6 / 117.6 / 203.5 / 203.5 mm 1338.0 x 1338.0 x 254.0 mm < 442 kg [TBD]
	Language	English
	Local Dimming Control	Yes
FEATURE	Support SNMP (Up to V3.0)	Yes
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	HDMI 2.1 (HDCP 2.3)	x6 (2160p)
INDLIT	DisplayPort	x2
INPUT	USB 3.0	x2
	Micro SD slot	x2
OUTPUT	Audio	x2
EXTERNAL	RS-232	x2
CONTROL	RJ-45	x4 (LAN)
	Operating Temperature	-30°~ 50° C
ENVIRONMENT	Storage Temperature	-20°~60° C
ENVIRUNMENT	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust resistant de	sign IP56
	Operating System	Android 8.0.0
	Processor	Dual-core A73 and dual-core A53
INTERNAL PLAYER	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2G
	Graphics	Quad-core MaliG51
ACCESSORY	Remote Control. Batteries	
ACCESSORY	Remote Control. Batteries	

Android is a trademark of Google LLC.

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.





**CERTIFICATION** CE / FCC / IEC60950-22 / RoHS