



HIK SERIES

P3.0 INDOOR LED DISPLAY

HIK series LED solutions deliver unrivalled versatility due to the variety of cabinet configurations available. Integrators specifying the HIK range have access to the broadest range of pixel pitch and aspect ratios options. Perfect for any internal space, these innovative Hisense LED modules include cable-less internal construction and full frontal access for ease of maintenance.



Highlights



High refresh rate

With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.



Brightness nits

With an average 500 nits and 1,000 nits maximum brightness, the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



Low brightness & High gray level

LED display could reveal more details, including layers and colors, than traditional displays do.



160° High viewing angle

The extra wide 160° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.



High color calibration

LED display correction technology could uniformly lighten several hundred thousand LED lights, presenting a uniform display effect with the same brightness and color scale.



AOB Admixture on board

AOB Transparent glass on surface enhances the mixed light property with scratch resistance, water-proof & easy to clean.















Specifications

ш	IK.	$^{\sim}$	ries
11	111	ンヒ	כשוו

Divisi Dital	D2.0	
Pixel Pitch	P3.0	
LED Type	SMD2121 3in1	
Thickness	53.7mm	
Module Size (W H/mm)	240 x 270	
Cabinet Dimension (W H/mm)	480 x 540 / 480 x 270 / 240 x 540	
Cabinet Resolution	160 x 180	
Cabinet Weight (kg/panel)	≤7kg (480 x 540) / ≤4kg (480 x 270) / ≤4kg (240 x 540)	
Brightness (Nits)	500 (0-1000 Adjustable)	
Contrast Ratio	7000:1	
Maintanance	Front Access	
IP Rating	IP50	
Max Power Consumption (W/sqm)	≤650	
Avg Power Consumption (W/sqm)	≤150	
Viewing Angle	160°	
Refresh Rate (Hz)	3840	
Operating Enviroment	-10° to 40° / 10 to 90% Relative Humidity (non condensing)	
Life Span	100,000 Hours	

Display Dimensions

