



PPC-1529

15" Intel® Celeron® SoC Processor J1900 Fanless Plastic Chassis Touch Panel PC

- Onboard Intel® Celeron® SoC J1900 2.0GHz BGA Processor
- 1 SODIMM up to 8GB DDR3L SDRAM
- 1 CF, 2 USB, 1 COM & 1 Mini-PCle
- 2 Intel Gigabit LAN, 2W Amplifier
- Timer-Power-On
- Fanless Operation, VESA Compliance
- Programmable Function Key
- IP-65 Compliant Front Panel
- VESA Compliance

+ Spec

-System Information-

Processor	Intel® Celeron® J1900 4-Core 2.0GHz processor
Platform Controller Hub	Intel® Valleyview SoC
System Memory	1 x 204-Pin DDR3L 1066/1333MHz SO-DIMM up to 8 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec. and 1sec./step
H/W Status Monitor	Monitoring System Temperature, Voltage and FAN Status with Auto Throttling Control
SBC	EBM-BYT

Expansion

Expansion	1 x Mini PCIe Supports mSATA
-----------	------------------------------

Storage

Storage	1 x CompactFlash Type I/II Socket 1 x 2.5" Drive Bay
---------	---

Panel

LCD Size	15", 4:3
Display Type	XGA
Resolution	1024x768
Pixel pitch	0.297mm (H) x 0.297mm (V)
Luminance	300 cd/m2
Contrast ratio	2000
Viewing angle	88(U), 88(D), 88(L), 88(R)
Response time	16 ms
Backlight	LED
Touch Type	5 Wires resistive
Touch Light Transmission	80 %

I/O

USB Port	1 x USB 3.0 3 x USB 2.0
COM Port	1 x RS-232/422/485

Display

Graphic Chipset	Intel® Valleyview SoC integrated Graphics Supports dual display
Spec. & Resolution	HDMI:Max. resolution 1920x1200@ 60Hz

Audio

Audio Codec	Realtek ALC888S
Audio Interface	Line-Out
Speaker Output	2 x 2W

Certifications

Certification Information	CE FCC Class B
---------------------------	-------------------

Ethernet

LAN Chipset	2 x Intel® I210IT
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45

Power Requirement

DC Input	+12V ~ +26V
DC Input Connector	Lockable DC Jack
Power Mode	AT/ATX (ATX is default setting)
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter)

Mechanical & Environmental



Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	351 X 319 X 54mm
Weight	4.9Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Construction - Front	White Plastic
Construction - Rear	Gary Plastic
Software Support	
OS Information	Win 7 Win 8 Win 10 Linux
Ordering Information	
Ordering Information	PPC-1529-190-A4R Intel Celeron SoC J1900 2.0GHz/2G DDR3L/32G SSD/2GLAN/COM/SPK/VESA Stand/12~26V input/12V Adapter