



## PPC-2129

### 21.5" Intel® Celeron® SoC Processor J1900 Fanless Plastic Chassis Touch Panel PC

- > Onboard Intel® Celeron® SoC J1900 2.0GHz BGA Processor
- > 1 SODIMM up to 8GB DDR3L SDRAM
- > 1 CF, 2 USB, 1 COM & 1 Mini-PCle
- > 2 Intel Gigabit LAN, 2W Amplifier
- > Timer-Power-On
- > Fanless Operation, VESA Compliance
- > Programmable Function Key
- > IP-65 Compliant Front Panel
- > VESA Compliance

#### + Spec

-System Information-	
<b>Processor</b>	Intel® Celeron® J1900 4-Core 2.0GHz processor
<b>Platform Controller Hub</b>	Intel® Valleyview SoC
<b>System Memory</b>	1 x 204-Pin DDR3L 1066MHz SO-DIMM up to 8 GB 204-Pin DDR3L 1600MHz SO-DIMM Processor J1900 only support 1333MHz
<b>I/O Chipset</b>	EC ITE IT8528E
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec. and 1sec./step
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
<b>SBC</b>	EBM-BYT
Expansion	
<b>Expansion</b>	1 x Mini PCIe Supports mSATA
Storage	
<b>Storage</b>	1 x CompactFlash Type VII Socket 1 x 2.5" Drive Bay
Panel	
<b>LCD Size</b>	21.5"
<b>Display Type</b>	Full HD
<b>Resolution</b>	1920x1080
<b>Pixel pitch</b>	0.248mm (H) x 0.248mm (V)
<b>Luminance</b>	250 cd/m2
<b>Contrast ratio</b>	3000
<b>Viewing angle</b>	89 (U), 89 (D), 89 (L), 89 (R)
<b>Response time</b>	18 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	5 Wires resistive
<b>Touch Light Transmission</b>	80%
I/O	
<b>USB Port</b>	3 x USB 2.0 1 x USB 3.0
<b>COM Port</b>	1 x RS-232/422/485
Display	
<b>Graphic Chipset</b>	Intel® Valleyview SoC integrated Graphics Supports dual display
<b>Spec. &amp; Resolution</b>	DP:Max. resolution 2560x1080@ 60Hz HDMI:Max. resolution 1920x1200@ 60Hz
Audio	
<b>Audio Codec</b>	Realtek ALC888S
<b>Audio Interface</b>	Line-Out
<b>Speaker Output</b>	2 x 2W
Certifications	
<b>Certification Information</b>	CE FCC Class B
Ethernet	
<b>LAN Chipset</b>	2 x Intel® I210IT
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Power Requirement	
<b>DC Input</b>	+12V ~ +26V
<b>DC Input Connector</b>	Lockable DC Jack



<b>Power Mode</b>	AT/ATX (ATX is default setting)
<b>Adapter</b>	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter)
<b>Mechanical &amp; Environmental</b>	
<b>Operating Temperature</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temperature</b>	-10°C ~ 50°C (14°F ~ 122°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	542 x 382 x 63mm
<b>Weight</b>	7.2Kgs
<b>Vibration Test</b>	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
<b>Shock Test</b>	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	White Plastic
<b>Construction - Rear</b>	Gary Plastic
<b>Software Support</b>	
<b>OS Information</b>	Win 7 Win 8 Win 10 Linux
<b>Ordering Information</b>	
<b>Ordering Information</b>	PPC-2129-190-A4R Intel Celeron SoC J1900 2.0GHz/2G DDR3L/32G SSD/2GLAN/COM/SPK/VESA Stand/12~26V input/12V Adapter