

AI Rugged Computer

COMPACT AI Rugged Vehicle Series

Computer Vision Edge Unit with NVIDIA Jetson AGX Xavier

LTE / GNSS / Wi-Fi



Dual nanoSIM
microSD
HDMI
USB

Image similar

DC supply

RS232

2 x CAN
M12 a-coded

2 x LAN
M12 x-coded

USB
3.1

Digital
I/Os

RPC/COMPACT RSL A3 (E2)

This fanless RPC COMPACT-A3 is based on the NVIDIA Jetson AGX Xavier processor module and offers a wide range of highly integrated interface options.

The ultra rugged and uncompromising design allows the use in the most demanding AI applications on mobile systems as well as in outdoor applications with harsh environmental conditions and guarantees long-term availability.

- 24/7 continuous operation
- Extended AI computing
- Wide temperature range
- Sealed housing with IP67, IP69 protection
- Shock and vibration resistant

 **NVIDIA.**
Linux for Tegra (L4T)



Product Highlights

Ultra rugged
Sealed housing, protection class IP67 & IP69
Maintenance free
Power Ignition controller
No moving parts / passively cooled
Pressure equalization membrane
Resistance to chemicals
Long term availability (fixed BOM)

Product Features

AGX Xavier or AGX Xavier Industrial
512-core NVIDIA Volta™ GPU
8-Core ARM v8.2 64-bit NVIDIA Carmel CPU
32GB 256-Bit LPDDR4x RAM soldered on board
NVMe M.2 2280 storage options
Ethernet, RS232, Digital I/O, USB 3.1, CAN-FD
SAE J1939 support
Rugged M12 connectors

Industries

Agriculture
Construction
Transportation
Off-Highway Vehicles
Heavy Industry
Autonomous Mobile Robots (AMRs)
Outdoor applications

Processor module / Performance			
NVIDIA Jetson AGX Xavier 32GB RAM 512-core NVIDIA Volta™ GPU with 64 Tensor Cores		•	•
8-Core ARM v8.2 64-bit NVIDIA Carmel CPU		•	•
AI Performance		32 TOPs	32 TOPs
NVIDIA Jetson AGX Xavier 64GB RAM 512-core NVIDIA Volta™ GPU with 64 Tensor Cores		on request	on request
NVIDIA Jetson AGX Xavier Industrial 512-Core NVIDIA Volta™ GPU (ECC) with 64 Tensor Cores		on request	on request
Memory / Storage			
Data L3 Cache Size		4MB	4MB
256-Bit LPDDR4x RAM soldered on board		32GB	32GB
eMMC 5.1 Flash Storage on board		32GB	32GB
microSD Card socket		1	1
M.2 2280 Key M socket (for NVMe SSD) ²		1	1
Features			
Inertial measurement unit (IMU) <small>STMicroelectronics ISM330DHCXTR</small>		•	•
Real time clock (RTC) with battery backup <small>Renata CR2477 (950 mAh)</small>		•	•
Communication Interfaces			
Display output <small>behind the back service cover</small>	(1x Standard HDMI connector)	HDMI 2.0	HDMI 2.0
Internal USB version 2.0 OTG <small>behind the back service cover</small>	(micro USB Type AB)	1	1
USB version 2.0 <small>behind the back service cover</small>	(Type A)	2	2
Ethernet 10/100/1000 Mbit BASE-T	(M12 female x-coded)	2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated	(M12 female a-coded)	2	2
Digital I/O's, 12/24VDC ¹	(M12 male a-coded)	4 in & 2 out	4 in & 2 out
Serial RS232 <small>RX, TX, RTS, CTS, GND</small>	(M12 male a-coded)	1	1
USB version 3.1 (5Gbit/s)	(Type A, IP67)	1	1
Mini PCIe socket ²		1	1
PPS Input ¹ , 3.3V (LVCMOS), connected to Xavier GPIO	(1x SMA)	on request	on request
Power over Ethernet - IEEE802.3at 10/100/1000Mbit ¹ , taller housing: h103mm	(M12 female x-coded)	on request	on request
GMSL2 camera inputs ¹ , taller housing: h103mm	(4x/8x FAKRA-Z)	on request	on request
Wireless Connectivity			
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS ⁶ , Sierra Wireless EM7590 (Dual nano SIM support)		3x SMA	on request
Wireless LAN (Wi-Fi 5) 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 5.1 ¹ Intel Wireless-AC 9260		2x RP-SMA	on request
Cellular 5G module (4G/3G fallback) with GNSS		on request	on request
Wireless LAN (Wi-Fi 6) 802.11ax/ac/a/b/g/n dual-band 2x2 MIMO		on request	on request
High Accuracy (RTK) GNSS positioning module with optional heading support ¹ u-blox ZED F9R / F9P		on request	on request
Technical Data			
Dimensions mm (housing, excl. mounting)		w250 x h75 x d170	w250 x h75 x d170
Net weight in gram		~3050	~3000
Non isolated input voltage, with Ignition controller <small>reverse polarity protected</small>		(M12 5P male a-coded)	
		9 ... 45VDC	9 ... 45VDC
Power consumption ³		depends on power mode (15W, 30W, MAXN)	
Environmental Conditions			
Operating temperature ³		-25°C ... +65°C	-25°C ... +65°C
Storage temperature		-25°C ... +80°C	-25°C ... +80°C
Ingress protection standard according to EN60529 (ISO 20653)		IP67 / IP69	IP67 / IP69
Conformal coating ⁴		on request	on request
Road vehicles, UN/ECE R10 (E-mark) ⁵		on request	on request
Shock ISO 15003 / EN60068-2-64 (designed to meet)		•	•
Vibration ISO 15003 / EN60068-2-64 (designed to meet)		•	•
EMI-Conformity		EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)		EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)		RED	RED
MTBF @ 25°C ambient <small>according to Telcordia SR-332, Environment GB, excluding battery</small>		~300 000h	~400 000

¹ Please contact factory for minimum order quantities² Internal connector³ Depending on installation situation, power mode and interface connection. See user documentation.⁴ On all possible components (excl. NVIDIA Xavier Module, connectors and wireless devices)⁵ UN/ECE-R10 is the type-approval test for European automotive electronics. It includes a variety of testing including RF immunity and emissions, transient immunity and emissions.⁶ The first versions of this product, featured the Sierra Wireless EM7455 LTE module (RPC/SLA3K22-M132S), this has been switched to the EM7590 for mass production, due to the EM7455 being EOL.

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogik Datentechnik AG
All rights reserved

Syslogik Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 1.0 | January 2023

For further information and support:
info@syslogik.com
support@syslogik.com
www.syslogik.com

+41 56 200 90 40
+49 7741 9671-420

Switzerland (Headquarters)
Germany and Austria

 **syslogik**
industrial computing