

AR-DP080VW

8-Inch(16:9) Display Monitor with VGA, USB Touch Screen and
DC 9-32V Input for Car PC and In-Vehicle Application



Features



- ✓ 8-Inch(16:9) Wide Screen
- ✓ LED Backlight with Low Power Consumption
- ✓ Resistive Touch Screen
- ✓ VESA75 Mounting and Stand
- ✓ DC 9-32V Power Input

In-Vehicle Computer

Specification

Panel

| | |
|-------------------------------------|---|
| Panel Size | 8-Inch Wide Screen (16:9) |
| Resolution | Supports from 640 x 480~1024 x 768 pixels |
| Luminance (cd/m²) | 500 nits |
| View Angle (H/V) | H:120 / V:100 |
| Backlight Lifetime | 20,000 hours |
| Touch Screen Type | 4-wire resistive |

I/O

| | |
|------------------------|--------------------------|
| Video Interface | 1 x VGA |
| USB | 1 x USB for Touch Screen |
| Audio | 1 x 3.5mm stereo Jack |

Power Requirement

| | |
|--------------------|----------|
| Power Input | DC 9~32V |
|--------------------|----------|

Software

| | |
|-----------------------------|--|
| Touch Driver Support | Windows: Vista, 9X, Me, NT4.0, 2000, XP, CE.net, CE 2.12, CE 3.0, Embedded, Dos. Mac: Mac OS 9X, OS X (Intel CPU). Linux: Linux Readme, Mandrake, Red Hat, Fedora Core, SuSE, Debian, Ubuntu, Yellow Dog |
|-----------------------------|--|

Mechanical & Environment

| | |
|------------------------------|-------------------------------|
| Chassis Material | Plastic |
| Dimension (W x H x D) | 220 x 135 x 29 mm (W x H x D) |
| Mounting | VESA 75, Metal Stand |
| Operating Temp. | -30~85°C |
| Storage Temp. | -40~95°C |
| Relative Humidity | - |
| Safety | CE, FCC |

Packing List

- User Manual x 1
- Metal Stand x 1
- All-in-One Cable x 1 (VGA / USB / DC Jack / Audio)
- Remote Controller x 1
- Touch Driver CD x 1
- Touch Stylus x 1
- Car Cigarette Lighter Adapter x 1
- AC Switching Power Supply x 1

Dimension

