

Open-Frame Touch Monitor

Full Range of Tailor-Made Touch Monitor with Variety Panel Options and JIS Z 2801 Antimicrobial Touchscreen

Features

- Variety of popular touch screen sizes from 21.5" to 55" and customized screen sizes
- Brightness from 250 nits to 1000 nits
- Support min. 30K/min. 50K hours panel backlight lifetime
- QLED up to 100% NTSC (optional)
- JIS Z 2801 certified antimicrobial glass (optional)
- Product longevity fulfill industry applications



Specifications

Screen Size	21.5" to 55"
Touchscreen	Projected Capacitive Touch (optional)
Resolution	1920 x 1080
Cover Glass	Customizable cover glass or JIS Z 2801 certified antimicrobial glass (optional)
Brightness	250 nits to 1000 nits
Input Signal	DP, DVI, VGA
Industry Design	Standard/Side LED strip/Full-frame LED strip

Odering Information

Model	Size	Resolution	Active Area (mm)	Brightness (Typ.)	Industry Design
GM212	21.5"	1920 x 1080	476.64 x 268.11	250 nits	Standard
GM232	23.8"	1920 x 1080	527.04 x 296.46	250 nits	Standard
GM234	23.8"	1920 x 1080	527.04 x 296.46	400 nits	Standard
GM275	27"	1920 x 1080	597.60 x 336.15	500 nits	Full-frame LED strip

