GOT3157W-881-PCT

15.6" WXGATFT Fanless Multi-touch Panel Computer with LGA1150 Socket 4th Gen Intel® Core™ i7/i5/i3. Pentium® & Celeron® Processors (0°C to +40°C)

Features

- 15.6" WXGA projected capacitive multi-touch screen
- Fanless design with LGA1150 socket 4th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processors (Haswell)
- 2.5" 7/9.5 mm SATA HDD, CFast™ and mSATA
- WLAN module and antenna (optional)
- 2 Gigabit LANs, 2 USB 3.0, 2 USB 2.0 & 2 COM ports
- IP65 front bezel and rugged design
- Supports panel mount and optional VESA arm/desktop stand/ wall mount
- 2 PCI Express Mini Card slots



















Introduction

The GOT3157W-881-PCT adopts a 15.6-inch WXGA LCD and supports LGA1150 socket 4th generation Intel® Core™, Pentium® and Celeron® processors. It can run Windows® 7, Windows® 7 Embedded, Windows® 8, Windows® 8 Embedded for a variety of applications. This 15.6" WXGA industrial touch panel PC has abilities below to make it surely a robust and reliable solution.

High Performance Haswell Desktop Processor

The GOT3157W-881-PCT supports LGA1150 socket 4th generation Intel® Core™ and Celeron® Haswell processors. Users can choose different processor upon request. It also supports up to 8 GB DDR3-1333/1600 MHz memory. Rich I/O includes dual PCI Express Mini Card slots, 2.5" HDD drive bay, USB 3.0 port, RS-232/422/485 and HDMI interface.


Reliable and Stable Design

The GOT3157W-881-PCT is a fanless cooling panel system designed for industrial machinery market. The Intel® Haswell panel PC can work under 1.0 G (10 ~ 500Hz, random for CFast™ card) in operation mode with a patent of anti-vibration design. The patent improves the system reliability and sustainability.

15.6-inch WXGA LCD with Projected Capacitive Multi-touch

The 15.6" WXGA Intel® Haswell-based touch panel PC supports 400 nits high brightness and can display contents in HD resolution. With projected capacitive multi-touch screen, users can operate more intuitively and directly. The hardness of touch glass surface is up to 7h and is better for anti-scratch purpose.





- 1. Power switch (ATX)
- 2. Power input connector
- 3. Audio (Line-out)
- 4. Audio (Mic-in)
- 5. COM 1/2 (RS-232/422/485)
- 6. HDMI output
- 7. Gigabit LAN x 2 8. USB 2.0 x 2
- 9. USB 3.0 x 2
- 10. CFast™ card slot
- 11. Antenna x 3
- 12. LED backlight power On/Off
- 13. Brightness +
- 14. Brightness -

Specifications

Front Bezel	IP65 front bezel		
LCD Panel	Display Type 15.6" WXGA TFT LCD		
	Brightness (cd/m²)	400 nits	
	Resolution	1366 x 768	
Main System	CPU	LGA1150 socket 4th generation Intel® Core™ i7/i5/i3, Pentium® Celeron® processors (Haswell), up to 45 W TDP	
	Chipset	Intel® H81	
	System Memory	1 x 204-pin DDR3-1333/1600 SO-DIMM, up to 8GB	
	BIOS	AMI UEFI BIOS	
	Storage	1 x 2.5" 7/9.5 mm SATA HDD 1 x CFast™ card 1 x mSATA	
	Watchdog Timer	255 levels, 0~255 sec.	
	Onboard Graphics	Integrated Intel® HD Graphics	

Specifications

I/O Connector	2 x RS-232/422/485 (COM 1/2)		
	1 x Switch for power on/off (ATX)		
	2 x Audio (Line-out & Mic-in)		
	2 x USB 3.0		
	2 x USB 2.0		
	1 x HDMI		
	2 x 10/100/1000 Mbps Ethernet (Intel® i219LM/i211AT)		
Expansion Interface	2 x PCI Express Mini Card slot		
Touchscreen	Projected capacitive multi-touch		
Power Supply	19 VDC with adapter		
Power Consumption	100 W		
Dimensions	396.8 mm (15.6") (W) x 89.5 mm (3.5") (D) x 247.1 mm (9.73") (H)		
Packing Dimensions	525 mm (20.67") (W) x 186 mm (7.32") (D) x 470 mm (18.51") (H)		
Weight (net/gross)	5.5 kg (12.13 lb)/7.5 kg (16.53 lb)		
Environment	Operating temperature: 0°C ~ +40°C (+32°F ~ +104°F)		
	Relative humidity: 20% ~ 90% @ 40°C; non-condensing		
	Operation vibration:		
	1.0 G, 10 ~ 500 Hz, random for CFast™ card		
Certificate	CE		

Ordering Information

G0T3157W-881-PCT-NP	15.6" WXGA TFT fanless touch panel computer with LGA1150 socket 4th generation Intel® Core™ i7/i5/i3, Pentium® & Celeron® processors, projected capacitive multi-touch screen and AC-DC 19 VDC power adapter (power DIN 4P connector)

Optional Accessories

82231770050E	GOT3177T-834 wall mount kit

Optional EOS Installation

١	Λ	/	E	8	S
١	۸	/	_	c	-

Optional OS Installation


Windows® 8.1 Windows® 7





▲ Ideal for factory automation & self-service kiosk in retail


Dimensions


Updated Apr. 11, 2018.














© 2017 Axiomtek Co., Ltd. All rights reserved.