

	DLF0705-T	DLH0705-T	SLD0705-T
Description	7" TFT LCD, 1000 nits LED backlight, 1024x800	7" TFT LCD, 1000 nits LED backlight, 1024x800	7" TFT LCD, 1000 nits LED backlight, 1024x800
Screen size	7"	7"	7"
Display area (mm)	149.76(H) x 93.6(V)	149.76(H) x 93.6(V)	149.76(H) x 93.6(V)
Brightness	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²
Resolution	1280x800	1280x800	1280x800
Aspect ratio	16:10	16:10	16:10
Contrast ratio	800:1	800:1	800:1
Pixel pitch (mm)	0.117 (H) x 0.117 (V)	0.117 (H) x 0.117 (V)	0.117 (H) x 0.117 (V)
Pixel per inch (PPI)	215	215	215
Viewing angle	176° (H), 176° (V)	176° (H), 176° (V)	176° (H), 176° (V)
Color saturation (NTSC)	50%	50%	50%
Display colors	16.7M	16.7M	16.7M
Response time (Typical)	35ms	35ms	35ms
Video interface	LVDS	VGA, DVI-D, HDMI	VGA, DVI-D, HDMI
Input power		DC 12V	DC 12V
Power consumption	TBD	TBD	TBD
Dimensions (mm)	161x107x4.5	161x107x4.5	TBD
Bezel size (U/B/L/R)	TBD	TBD	TBD
Weight (Net)	85kg	85kg	TBD
Mounting			TBD
OSD key		4 keys (Power switch, menu, +, -)	4 keys (Power switch, menu, +, -)
OSD control		Brightness, color, contrast, H/V position... etc	Brightness, color, contrast, H/V position... etc
Operating temperature	-20°C ~ +70°C	-20°C ~ +70°C	-20°C ~ +70°C
Storage temperature	-30°C ~ +80°C	-30°C ~ +80°C	-30°C ~ +80°C
Product approval			TBD