

L-8018

8 Isolated Analog Thermocouple Temperature Input Module



Features

- ◆ Support Thermocouple J, K, T, R, S, E, B, N, C Type
 - ◆ Protocol MODBUS RTU, ASCII Command
 - ◆ Support Isolated Input Channels
 - ◆ Fully Photo-Isolation 3750Vrms
 - ◆ Wide Supply Voltages (10~30V)

Built-In TVS/ESD Protection

Burn-Out Auto Detection

Specifications

Interface:

Communication	RS485	Zero Drift	$\pm 0.5\mu V / ^\circ C$
Protocol	MODBUS RTU and ASCII Command	Span Drift	25 ppm / $^\circ C$
Baute Rate (bps)	1200, 2400, 4800, 9600, 19.2K, 38.4K, 115.2K	CMRR	50/60 Hz: 92 dB
LED Indication	LED for Power	Burn-Out	Wire burn-out auto detection
Isolation Voltage	3000VDC	Over Voltage Protection	$\pm 60V$

Analog input:

Effective Resolution	16-bit
Input Channels	8 channel
Input Type	Voltage, Current, Thermocouple
Input Range	$\pm 15\text{mV}$, $\pm 50\text{mV}$, $\pm 100\text{mV}$, $\pm 500\text{mV}$, $\pm 1\text{V}$, $\pm 2.5\text{V}$, $\pm 20\text{mA}$
Thermocouple Type	J, K, T, R, S, E, B, N, C
Isolation Voltage	3750Vrms
Sampling Rate	10 Samples / Second
Input Impedance	4.5M ohm
Accuracy	$\pm 0.1\%$ or better

Power requirement :

Consumption	0.8 W/Typical
Power Input	+10 ~ +30 VDC
Humidity	5 ~ 95% RH, non-condensing

Block Diagram

