

L1203S-RT

Specification

Plastic case, 12.1" LCD monitor, 1024x768, 400nits



Features

- The best communication interface, user friendly controls allow you to operate your monitor easily so you can devote your full attention to the fabulous images on screen.
- Mouse and keyboard free, use your fingers directly, easy to use for POS display, information board, industrial field, medical and transportation.
- The stable removable base is engineered for the physical demands of touch screen use. The sturdy design helps foster intuitive operator entry and flexibility with a variety of applications to help reduce training time and costs and operational errors and help increase employee productivity and customer satisfaction.

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4 : 3 / 12.1" viewable diagonal area	
	Active Area / Pixel Pitch	245.8(H) x 184.3(V) mm / 0.24(H) x 0.24(V) mm	
	Native Resolution / Colors	1024(H) x 768(V) / 262 K	
	Brightness / Contrast	400 cd/m ² (typ) / 500 : 1	
	Response Time	≤ 16 ms	
	Viewing Angle (typical)	H. 90° (- 45° ~ + 45°) , V. 65°(- 45° ~ + 20°)	
	Light Source	CCFL , Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F _n : 30 - 82Khz , F _v : 50 -75Hz
	Audio System	2W speaker x 2	
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)		
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
Power Consumption	Operation / Power Saving	20 watt , < 2 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	With Base(W x H x D) : 320.8 x 280 x 190 mm	
		Without Base(W x H x D) : 320.8 x 266 x 40.5 mm	
	Carton	W x H x D = 370 x 349 x 149 mm	
Weight	N.W. / G.W.	3.0 Kgs / 4.0 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)	

Touch (Option)	Resolution	Transparency	Linearity	Durability	Driver
Resistive	2048 x 2048	80% ± 3%	X ≤ 1.0%, Y ≤ 1.0%	35 Million Times	MS-OS, Linux, QNX
Capacitive	2048 x 2048	88% ± 2%	X ≤ 1.0%, Y ≤ 1.0%	200 Million Times	MS-OS, Linux, QNX

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

www.ewinsonic.com