

Lanolinx LNX-500AG

5-Port 10/100/1000T Slim Industrial Switch




Features

- ▶ RJ-45 Port Supports Auto MDI/MDI-X Function
- ▶ Store-and-Forward Switching Architecture
- ▶ 10Gbps Back-Plane (Switching Fabric)
- ▶ 136Kbits Memory Buffer
- ▶ 8K MAC Address Table
- ▶ 9Kbytes Jumbo Frame
- ▶ Wide-Range Redundant Power Design
- ▶ Power Polarity Reserve Protect
- ▶ Overload Current Resettable Fuse Present
- ▶ Supports 4000 VDC Ethernet ESD Protection
- ▶ IP30 Rugged Aluminum Case Design
- ▶ DIN-Rail and Wall Mount Design
- ▶ 5-Year Warranty



▶ Dimensions (unit = mm)



► Specifications

Standard

IEEE 802.3 10BaseT Ethernet
IEEE 802.3u 100BaseTX
IEEE 802.3ab 1000BaseT
IEEE 802.3x Flow Control and Back-Pressure

Protocol

CSMA/CD

Switch Architecture

Back-Plane (Switching Fabric): 10Gbps
Packet Throughput Ability (Full-Duplex): 14.88Mpps @ 64bytes

Transfer Rate

14,880pps for Ethernet Port
148,800pps for Fast Ethernet Port
1,488,000pps for Gigabit Ethernet Port

Memory Buffer

136 Kbits

MAC Address

8K MAC Address Table

Jumbo Frame

9 Kbytes

LED

Unit: Power 1, Power 2, Fault
Port: Link/Activity, Speed

Connector

10/100/1000T: 5 x RJ-45

Network Cable

10BaseT: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m)
100BaseTX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m)

Power Supply

DC 12 ~ 48V, Redundant Power with Polarity Reverse Protect Function and Removable Terminal Block

Power Consumption

5 Watts (Open Issue)

Reverse Polarity Protection

Present

Overload Current Protection

Present

Mechanical

Casing: IP30 Metal Case
Dimension (W x H x D): 30 x 140 x 95 mm (1.18 x 5.51 x 3.74 in.)
Installation: DIN-Rail/Wall Mountable

Weight

Unit Weight: 1 lbs.
Shipping Weight: 1.5 lbs.

Operation Temperature

Standard: -10° C to 70° C (14° F to 158° F)
Wide Operating Temperature: -40° to 80° C (-40° to 176° F)

Operation Humidity

5% to 95% (Non-condensing)

Storage Temperature

-40° C to 85° C

EMI

FCC Class A
CE EN6100-4-2/EN6100-4-3/EN6100-4-4/EN6100-4-5/EN6100-4-6
/EN6100-4-8/EN6100-4-11/EN6100-4-12/EN6100-6-2/EN6100-6-4

Safety

UL, cUL, CE EN60950-1

Stability Testing

Shock: IEC60068-2-27
Free Fall: IEC60068-2-32
Vibration: IEC60068-2-6

Warranty

5-Year Warranty

► Ordering Information

LNX-500AG

5-Port 10/100/1000T Slim Industrial Ethernet Switch

LNX-500AG-T

5-Port 10/100/1000T Slim Industrial Ethernet Switch, Wide Operating Temperature

Optional Accessories

DR-4524

45W 24VDC Industrial DIN Rail Power Supply

DR-75-24

75W 24VDC Industrial DIN Rail Power Supply

DR-120-24

120W 24VDC Industrial DIN Rail Power Supply

Aaxeon Technologies

445 Capricorn St.
Brea, CA 92821
USA

Toll-Free: (877) AAXEON5 (229-3665)
Phone: (714) 671-9000
FAX: (714) 671-9944
e-Mail: info@aaxeon.com

aaxeon
www.aaxeon.com