


# POC-465AWP

IP65 Waterproof Computer with Intel<sup>®</sup> Atom<sup>®</sup> x6425E, 2x 2.5GbE and Isolated COM Ports



#### Introduction

POC-465AWP is a new segment of Neousys fanless computers featuring an IP65 rating based on Intel<sup>®</sup> Elkhart Lake Atom. The acronym AWP stands for affordability, waterproof, and protection. In short, the POC-465AWP is designed to solve your everyday environmental challenges. With IP65 waterproof protection in a stainless steel and aluminum chassis, the air-tight system prevents internal PCBA corrosion in high salinity or humidity situations. Secondly, the hermetic enclosure can be deployed into grimy or dusty air-polluted environments such as a farm or mining site without being affected. The system also features -25°C to 70°C wide operating temperature capability and an efficient heat dissipation design to minimize thermal throttling.

Connection-wise, POC-465AWP comes with M12 connectors to ensure connection in demanding, shock, and vibration environments. The system has two 2.5G Ethernet ports, one isolated RS-232, and one isolated RS-422/485. The isolated design protects the motherboard from voltage spikes that may damage internal components. It also has VGA and two USB2.0 ports. The POC-465AWP features M.2 B key support wireless LTE/ 5G communication, and it also supports M.2 Key M SATA interface for SSD storage.


Combining IP65, M12 and great thermal design, POC-465AWP is reliable and highly tolerant to challenging conditions to fulfill versatile applications. Its ultra-compact size fits easily into confined spaces, and its waterproof capability makes it suitable for outdoor applications like wildfire detection, unmanned vehicle; or harsh environments like food / beverage manufacturing and pharmaceutical processing. The IP65 rating is an additional function that can enhance a product's value and quality, and such is the case with Neousys' POC-465AWP.


## Specifications

System Core		Power Supply	
Processor	Intel <sup>®</sup> Elkhart Lake Atom <sup>®</sup> x6425E quad-core 2.0GHz/ 3.0GHz 12W processor	DC Input	8~35V DC input with ignition power control input via M12 A-coded, 5-pin connector
Graphics	Integrated Intel <sup>®</sup> HD Graphics	Mechanical	
Memory	Up to 32 GB DDR4-3200 SDRAM by one SODIMM socket	Dimension	106 mm (W) x 159.7 mm (D) x 79 mm (H)
ТРМ	Supports TPM 2.0 (fTPM/ dTPM)	Weight	1.45kg
I/O Interface		Mounting	Wall-mount (optional)
Ethernet	2x 2.5G Ethernet ports by Intel <sup>®</sup> I225-IT / I226-IT via M12 X-coded, 8-pin connector 1x VGA connector, supporting 1920 x 1200 resolution, via M12 A-coded, 17-pin connector 1x isolated RS-232 port (COM1) and 1x isolated RS-422/485 ports (COM2) via M12 A-coded, 8-pin connector	Environmental	
Ethernet		Operating	-25°C ~ 70°C
		Temperature	-25 C 70 C
		Storage Temperature	-40°C ~ 85°C
Serial Port		Humidity	10%~90% , non-condensing
USB	2x USB 2.0 ports via M12 A-coded, 8-pin connector	Vibration	Operating, MIL-STD-810G, Method 514.6, Category 4
Storage Interface		Shock	Operating, MIL-STD-810G, Method 516.6, Procedure I, Table 516.6-II
M.2	1x M.2 2280 M key socket for SATA SSD	EMC	CE/FCC Class A, according to EN 55032 & EN 55035
Internal Expans	sion Bus	-	
M.2	1x M.2 2242/3052 B key socket for 4G/5G module	-	



### Appearance





## **Ordering Information**

Model No.	Product Description
POC-465AWP	IP65 Waterproof Computer with Intel <sup>®</sup> Atom <sup>®</sup> x6425E, 2x 2.5GbE and Isolated COM Ports

## **Optional Accessories**

PA-60W-OW	60W AC/DC power adapter with 12V, 5A DC output, cord end terminals for terminal block. Operating temperature : -30 to 60 °C
M12-Cable-Kit-POC-465AWP	2x LAN, 1x VGA, 2x USB2.0 (by Y-cable), 2x COM (by Y-cable) and DC power cables
Wmkit-POC465AWP	Wall-mount assembly for POC-465AWP