



19" Flat P-CAP Marine Display

Model#: R19L300-MRA1FP


Features:

- 19" 1280 x 1024 resolution with projective capacitive multi-touch screen
- Edge-to-edge narrow bezel design and fanless cooling system
- Color calibrated for ECDIS compliance
- · Capacitive touch keys for quick function access and display control (Support ECDIS DAY, DUSK, and NIGHT mode switching)
- Compliant with marine standards (DNV2.4, IEC 60945 4th, IACS-E10)









* Note: this is a simplified drawing and some components are not marked in detail. *Please contact our sales representative if you need further product information.

Display Specifications:

Resolution : 1280 x 1024 Pixel Pitch

: 0.294 (H) x 0.294 (V) mm

Contrast Ratio : 1000:1(typ.) Brightness : 350 cd/m² (typ.)

Viewable Angle : 85°/85°/80°/80° (typ.) (Up/Down/Left/Right) Active Display Area

: 376.32 (H) x 301.06 (V) mm Max Colors : 16.7 M colors, 8 bits/color Touch Screen : Projective Capacitive Multi-touch (Optional AR Protection Glass)

Buzzer : 75 dB~80 dB, 2300 Hz, 1m

User Controls:

OSD control via programmable capacitive touch keys (ECDIS, Home, Brightness(+,-), Power)

Remote control via RS232 serial interface

Mechanical

: Panel Mount, VESA Mount Mechanical Mounting 429mm x 382mm x 72.8mm Dimension

Panel Mount Cutout 408mm x 359mm Anodized Aluminum Bezel Housing

: IP66 (Front Side) IP Rating

Input / Output Connectors

RGB Signal IN : D-SUB 15pin connector (female) DVI-D Signal IN : DVI-D 24pin connector (female) : 3pin Terminal block (Phoenix type) DC Power IN Remote control : D-SUB 9pin connector (female) via RS232

Touch Signal OUT : USB type A connector (female)

Environmental

Operating Temperature -15 to 55 deg.C 5% to 95% (non condensing) Operating Humidity : 0.7g@DNV2.4 (Class A) Anti-Vibration : 15G,11ms duration Anti-Shock

Power Specifications:

: 24V DC-in with Isolation (9~36V acceptable) Power Input

Certification

DNV 2.4, IEC60945 4th, CE, FCC